



- Dual-color 12V-2x6 Cable
- ATX 3.1 Ready
- PCIe 5.1 Ready (300W)
- 80 PLUS Bronze
- 120mm Fan
- DC to DC power Design
- Active PFC Design
- Industrial level protection with OVP, OCP, SCP, OPP, UVP

SPECIFICATIONS

Efficiency Rating	80 PLUS Bronze (up to 85%)
Modular	No
Fan Size	120 mm
Fan Bearing	Hydraulic Bearing
Dimensions (DxWxH)	140mm x 150mm x 86mm / 5.51 x 5.9 x 3.38 inches
PFC Type	Active PFC
Input Voltage Range	100-240V~
Power Watt	650W
Power Excursion	200%
Input Frequency Range	50-60Hz
Protection	OVP, OCP, SCP, OPP, UVP
ATX (24 pin)	1
EPS (4+4 pin)	2
PCI-E 5.1 (16 pin)	1 (300W)
PCI-E (6+2 pin)	2
SATA (15 pin)	3
PERIPHERAL (4 pin)	2

MAG A650BN PCIE5 III				
AC INPUT		100-240V~, 10-5A, 50-60Hz		
DC OUTPUT	+5V	+3.3V	+12V	+5Vsb
	15A	15A	54A	2.5A
TOTAL POWER	100W		648W	12.5W
	650W			



POWER - SUPPLY

MAG A650BN PCIE5 III

YOUR POWER, RIGHT AWAY

CONNECTOR					
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL
1	2	1	2	3	2