



- Dual-color 12V-2x6 Cable
- ATX 3.1 Ready
- PCIe 5.1 Ready (600W)
- 105°C Main Electrolytic Capacitor
- 80 PLUS Platinum Certification
- Embossed Jacket Certified Cables
- Industrial level protection with OCP, OTP, OPP, SCP, OVP, UVP, SIP, NLO

SPECIFICATIONS

Efficiency Rating	80 PLUS Platinum (up to 92%)
Modular	Fully Modular
Fan Size	120 mm
Fan Bearing	Hydraulic Bearing
Dimensions (DxWxH)	150 x 150 x 86 mm / 5.9 x 5.9 x 3.38 inches
PFC Type	Active PFC
Input Voltage Range	100-240V~
Power Watt	1000W
Power Excursion	200%
Input Frequency Range	50-60Hz
Protection	OCP, OTP, OPP, SCP, OVP, UVP, SIP, NLO
ATX (24 pin)	1
EPS (4+4 pin)	2
PCI-E 5.1 (16 pin)	1 (600W)
PCI-E (6+2 pin)	3
SATA (15 pin)	6
PERIPHERAL (4 pin)	2

PRO A1000PL PCIE5

AC INPUT	100-240V~, 13-6.5A, 50-60Hz				
DC OUTPUT	+5V	+3V	+12V	-12V	+5Vsb
	20A	20A	83.3A	0.3A	2.5A
TOTAL POWER	100W	999.6W	3.6W	12.5W	
	1000W				

CONNECTOR



POWER-SUPPLY

PRO A1000PL PCIE5

YOUR POWER, RIGHT AWAY

CONNECTOR					
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL
1	2	1	3	6	2