



- 支援 Nvidia® GeForce RTX™ 50 系列顯示卡
- 原生 12V-2x6 連接埠
- 12V-2x6 雙色線材
- 80 PLUS 金牌認證
- 低噪設計
- Main 105°C 電容
- 壓花編織線材更加柔軟易彎曲，更容易整線。
- 工業保護機制，包含 OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO

SPECIFICATIONS

Efficiency Rating	80 PLUS Gold (up to 90%)
Modular	Yes (full modular)
Fan Size	135 mm
Fan Bearing	Fluid Dynamic Bearing
Dimensions (DxWxH)	150 x 150 x 86 mm
PFC Type	Active PFC
Input Voltage Range	100-240V~
Power Watt	850W
Power Excursion	1870W (*up to 220% of the PSU's rated power for 100µs)
Input Frequency Range	47-63 Hz
Protection	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO
ATX (24 pin)	1
EPS (8 pin)	2
PCI-E (6+2 pin)	4
SATA (15 pin)	8
MOLEX (4 pin)	3
FDD (4 pin)	1
PCI-E 5.1 (16 pin)	1 (600W)