

MAG A650GL



- 全模組化，扁平線材。
- 高效率 80 PLUS 金牌認證
- 主動式 PFC 設計，工業水準的保護機制，包含 OVP / OCP / OPP / OTP / SCP / UVP
- 120 mm 液態軸承風扇
- DC DC 模組的 LLC 全橋設計

SPECIFICATIONS

Efficiency Rating	80 PLUS Gold (up to 90%)
Modular	Yes (full modular)
Fan Size	120 mm
Fan Bearing	Fluid Dynamic Bearing
Dimensions (DxWxH)	140 x 150 x 86 mm
PFC Type	Active PFC
Input Voltage Range	100~240 VAC
Power Watt	650W
Input Frequency Range	47-63Hz
Protection	OCP / OVP / OPP / OTP / SCP / UVP
ATX (24 pin)	1
EPS (4+4 pin)	2
PCI-E (6+2 pin)	4
SATA (15 pin)	6
MOLEX (4 pin)	4
FDD (4 pin)	1

MAG A650GL					
AC INPUT	100-240~, 10A , 47-63Hz				
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	20A	20A	54A	0.3A	2.5A
TOTAL POWER	100W	648W	3.6W	12.5W	
	650W				

CONNECTOR						
ATX (20+4 PIN)	EPS (4+4 PIN)	PCI-E5.0	PCI-E (6+2 PIN)	SATA	MOLEX (PERIPHERAL)	FDD
1	2	0	4	6	3	1