

SPECIFICATIONS

| | |
|------------------------------|--|
| Efficiency Rating | 80 PLUS Titanium (up to 94%) |
| Modular | Yes (full modular) |
| Fan Size | 135 mm |
| Fan Bearing | Fluid Dynamic Bearing |
| Dimensions (DxWxH) | 190 x 150 x 86 mm |
| PFC Type | Active PFC |
| Input Voltage Range | 100-240V~ |
| Power Watt | 1600W |
| Input Frequency Range | 50-60 Hz |
| Protection | OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO |
| ATX (24 pin) | 1 |
| EPS (4+4 pin) | 1 |
| PCI-E (6+2 pin) | 7 |
| SATA (15 pin) | 8 |
| MOLEX (4 pin) | 4 |
| PCI-E 5.1 (16 pin) | 2 (600W) |

FEATURES



GPU SAFEGUARD+

Built-in overcurrent protection specific to the 12V-2x6 interface. The MSI CENTER software issues a real-time warning prompting the user to inspect the connection of the 12V-2x6.




SiC MOSFET

The server-grade materials, not only enhance power supply's stability, also reduce losses, and optimize heat dissipation.



FAN SAFEGUARD

The integrated fan failure protection immediately detects when the fan stops spinning. A buzzer will then sound, alerting you to the problem and preventing the power supply from overheating.



DUAL COLOR 12V-2x6 CONNECTOR

With its vibrant yellow connector, you can easily see if the cable is fully plugged in, which helps guarantee a secure connection.



OPTIMIZED THE SOUND LEVEL

This power supply is designed for quiet operation, delivering low noise levels like in the midnight, ensuring a serene computing experience free from disturbances.



EMBOSSED JACKET CABLE

The embossed cables are exceptionally flexible for easy routing and cable management, while also offering superior durability and a premium look.