



- Mendukung kartu grafis® NVIDIA GeForce RTX seri 50
- Konektor bawaan 12V-2x6
- Kabel 12V-2x6 dua warna
- Bersertifikasi 80 PLUS Gold
- Tingkat kebisingan dioptimalkan
- Kapasitor utama°105°C
- Kabel berjaket embossed, lebih lentur dan mudah dirutekan
- Perlindungan tingkat industri dengan fitur OCP, OTP, OPP, SCP, OVP, UVP, SIP, dan NLO

SPECIFICATIONS

WEIGHT (CARD)	169g
Efficiency Rating	80 PLUS Gold (up to 90%)
Modular	Yes (full modular)
Dimensions	120mm x 120mm x 25.6mm
Fan Size	135 mm
Fan Bearing	Fluid Dynamic Bearing
Dimensions (DxWxH)	150 x 150 x 86 mm
Bearing Type	Hydro-Dynamic Bearing
PFC Type	Active PFC
Rated Speed	500 - 1800 ±15% RPM
Power Watt	750W
Input Voltage Range	100-240V~
Power Excursion	1650W (*up to 220% of the PSU's rated power for 100µs)
Air Flow	19.79 - 71.27 CFM
Input Frequency Range	50-60 Hz
Static Air Pressure	0.16 - 2.09 mm-H2O
Protection	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO
ATX (24 pin)	1
Connector	4-Pin PWM/DC
Life Expectancy	MTTF 150,000 Hours (25°C)
EPS (4+4 pin)	2
PCI-E 5.1 (16 pin)	1 (450W)
PCI-E (6+2 pin)	4
SATA (15 pin)	5
MOLEX (4 pin)	2
FDD (4 pin)	1

MAG A750GLS PCIE5

AC INPUT 100-240V~, 10-5A, 50-60Hz



POWER - SUPPLY

MAG A750GLS PCIE5

MAG A750GLS PCIE5					
DC OUTPUT	+5V	+3.3V	+12V	+12V	+5Vsb
	18A	18A	62.5A	0.3A	2.5A
TOTAL POWER	100W		750W	3.6W	12.5W
	750W				

CONNECTOR						
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL	FDD
1	2	1	4	5	2	1