



- Siap untuk ATX 3.1, konektor PCIe 5.1 asli
- Mendukung kartu grafis NVIDIA® GeForce RTX™ 40 Series
- Kapasitor utama 105°C
- Bersertifikasi 80 Plus Gold untuk efisiensi tinggi dengan desain PFC Aktif
- Perlindungan tingkat industri dengan OVP, OCP, OPP, OTP, SCP
- Sleeve Bearing Fan ukuran 120 mm
- Topologi Full Bridge dengan desain modul DC-DC

SPECIFICATIONS

Efficiency Rating	80 PLUS Gold (up to 90%)
Modular	No (non modular)
Fan Size	120 mm
Fan Bearing	Sleeve Bearing
Dimensions (DxWxH)	140 x 150 x 86 mm
PFC Type	Active PFC
Power Watt	750W
Input Voltage Range	100~240 VAC
Power Excursion	1500W (*up to 200% of the PSU's rated power for 100µs)
Input Frequency Range	47-63Hz
Protection	OCP / OVP / OPP / OTP / SCP
ATX (24 pin)	1
EPS (4+4 pin)	2
PCI-E 5.1 (16 pin)	1
PCI-E (6+2 pin)	2
SATA (15 pin)	4
MOLEX (4 pin)	2

MAG A750GN PCIE5

AC INPUT	100-240~, 10A , 47-63Hz				
DC OUTPUT	+12V	+5V	+3.3V	-12V	+5Vsb
	62.5A	20A	20A	0.3A	3A
TOTAL POWER	750W	110W	3.6W	15W	
	750W				

CONNECTOR					
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL
1	2	1	2	4	2