



MPG A1250GS PCIE5

- Mendukung kartu grafis Nvidia® GeForce RTX™ 50 Series
- 2 x konektor asli 12V-2x6
- Kabel 12V-2x6 dua warna
- Bersertifikat 80 PLUS Gold
- Mengoptimalkan tingkat suara
- 100% semua kapasitor 105 C°kelas Server
- Embossed Jacket Cables, kabelnya lebih lentur dan mudah dirutekan
- Perlindungan tingkat industri dengan OCP/OTP/OPP/SCP/OVP/ UVP/ SIP/ NLO

SPECIFICATIONS

WEIGHT (CARD)	169g
Efficiency Rating	80 PLUS Gold (up to 90%)
Modular	Yes (full modular)
Dimensions	120mm x 120mm x 25.6mm
Fan Size	135 mm
Fan Bearing	Fluid Dynamic Bearing
Dimensions (DxWxH)	150 x 150 x 86 mm
Bearing Type	Hydro-Dynamic Bearing
PFC Type	Active PFC
Rated Speed	500 - 1800 ±15% RPM
Power Watt	1250W
Input Voltage Range	100-240V~
Power Excursion	2937W (*up to 235% of the PSU's rated power for 100µs)
Air Flow	19.79 - 71.27 CFM
Input Frequency Range	50-60 Hz
Static Air Pressure	0.16 - 2.09 mm-H2O
Protection	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO
ATX (24 pin)	1
Connector	4-Pin PWM/DC
Life Expectancy	MTTF 150,000 Hours (25°C)
EPS (4+4 pin)	2
PCI-E 5.1 (16 pin)	2 (600W)
PCI-E (6+2 pin)	1
SATA (15 pin)	8
MOLEX (4 pin)	4

MPG A1250GS PCIE5

AC INPUT	100-240V~, 15A, 50-60Hz				
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	22A	22A	104.1A	0.3A	3A



POWER - SUPPLY

MPG A1250GS PCIE5

MPG A1250GS PCIE5				
TOTAL POWER	120W	1249W	3.6W	15W
	1250W			

CONNECTOR					
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL
1	2	2	1	8	4