



- Supports Nvidia® GeForce RTX™ 50 series graphics cards
- Native 12V-2x6 connector
- Dual-color 12V-2x6 cable
- 80 PLUS Gold certified
- Optimized the sound level
- Main 105°C capacitor
- Embossed Jacket Cables, the cables are more bending and routing
- Industrial level protection with OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO

SPECIFICATIONS

Model Name	TORX FAN 12CM
WEIGHT (CARD)	169g
Dimensions	120mm x 120mm x 25.6mm
Modular	Yes (full modular)
Bearing Type	Hydro-Dynamic Bearing
Fan Bearing	Fluid Dynamic Bearing
Rated Speed	500 - 1800 ±15% RPM
Power Watt	850W
Input Voltage Range	100-240V~
Power Excursion	1870W (*up to 220% of the PSU's rated power for 100µs)
Air Flow	19.79 - 71.27 CFM
Static Air Pressure	0.16 - 2.09 mm-H2O
Input Frequency	47-63 Hz
Connector	4-Pin PWM/DC
Efficiency	80 PLUS Gold (up to 90%)
EPS (8 pin)	2
Life Expectancy	MTTF 150,000 Hours (25°C)
ATX (24 pin)	1
PCI-E 5.1 (16 pin)	1 (600W)
Fan Size	135 mm
Dimension	150 x 150 x 86 mm
PCI-E (6+2 pin)	4
PFC Type	Active PFC
SATA (15 pin)	8
Protection	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO
MOLEX (4 pin)	3
FDD (4 pin)	1