



- ATX 3.1 ready, native PCIe 5.1 connector
- Supports NVIDIA® GeForce RTX™ 40 Series graphics cards
- Full modular design, Flat cables
- 80 Plus Gold certified for high efficiency with Active PFC design
- Industrial level protection with OVP, OCP, OPP, OTP, SCP, UVP
- 120 mm Fluid Dynamic Bearing Fan
- LLC Full Bridge Topology with DC-DC module design

SPECIFICATIONS

Model Name	TORX FAN 12CM
WEIGHT (CARD)	169g
Dimensions	120mm x 120mm x 25.6mm
Modular	Yes (full modular)
Bearing Type	Hydro-Dynamic Bearing
Fan Bearing	Fluid Dynamic Bearing
Rated Speed	500 - 1800 ±15% RPM
Power Watt	750W
Input Voltage Range	100~240 VAC
Power Excursion	1500W (*up to 200% of the PSU's rated power for 100µs)
Air Flow	19.79 - 71.27 CFM
Static Air Pressure	0.16 - 2.09 mm-H2O
Input Frequency	47-63Hz
Connector	4-Pin PWM/DC
Efficiency	80 PLUS Gold (up to 90%)
Life Expectancy	MTTF 150,000 Hours (25°C)
ATX (24 pin)	1
PCI-E 5.1 (16 pin)	1 (450W)
Fan Size	120 mm
EPS (8 pin)	2
Dimension	140 x 150 x 86 mm
PCI-E (6+2 pin)	3
PFC Type	Active PFC
SATA (15 pin)	8
Protection	OCP / OVP / OPP / OTP / SCP / UVP
MOLEX (4 pin)	4
FDD (4 pin)	1

MAG A750GL PCIE5 II

AC INPUT

100-240~, 10A , 47-63Hz



POWER - SUPPLY

MAG A750GL PCIE5 II

MAG A750GL PCIE5 II					
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	20A	20A	62A	0.3A	2.5A
TOTAL POWER	110W		744W	3.6W	12.5W
	750W				

CONNECTOR						
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL	FDD
1	2	1	3	8	4	1