



- Semi-ModularE
- 80 PLUS Bronze
- Ventola da 120mm
- Progettazione di potenza da DC a DC
- Design Active PFC
- Protezione di livello industriale con OVP, OCP, SCP, OPP, OTP

SPECIFICATIONS

Model Name	TORX FAN 12CM
WEIGHT (CARD)	169g
Dimensions	120mm x 120mm x 25.6mm
Modular	Semi-Modular
Input Voltage Range	100-240~
Fan Bearing	Sleeve Bearing
Bearing Type	Hydro-Dynamic Bearing
Power Watt	750W
Rated Speed	500 - 1800 ±15% RPM
Air Flow	19.79 - 71.27 CFM
Static Air Pressure	0.16 - 2.09 mm-H2O
Input Frequency	50~60Hz
Efficiency	80 PLUS Bronze (up to 85%)
Connector	4-Pin PWM/DC
Life Expectancy	MTTF 150,000 Hours (25°C)
ATX (24 pin)	1
Fan Size	120 mm
EPS (4+4 pin)	2
Dimension	140mm x 150mm x 86mm / 5.51 x 5.9 x 3.38 inches
PCI-E (6+2 pin)	2
PFC Type	Active PFC
SATA (15 pin)	8
Protection	OCP, OVP, OPP, OTP, SCP
MOLEX (4 pin)	4
FDD (4 pin)	1

MAG A750BE

AC INPUT	100-240V, 10A , 47-63Hz				
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	20A	20A	62.5A	0.3A	2.5A



POWER-SUPPLY

MAG A750BE

YOUR POWER, RIGHT AWAY

MAG A750BE

TOTAL POWER	120W	750W	3.6W	12.5W
750W				

CONNECTOR

ATX	EPS	PCI-E	SATA	Molex	FDD		
1	2	2	8	4	1		