



- Dual-color 12V-2x6 Cable
- ATX 3.1 Ready
- PCIe 5.1 Ready (450W)
- 80 PLUS Bronze
- Ventola 120mm
- DC to DC power Design
- Active PFC Design
- Protezione di livello industriale con OVP, OCP, SCP, OPP, UVP

## SPECIFICATIONS

<b>Modular</b>	No
<b>Input Voltage Range</b>	100-240V~
<b>Fan Bearing</b>	Hydraulic Bearing
<b>Power Watt</b>	750W
<b>Power Excursion</b>	200%
<b>Input Frequency</b>	50-60Hz
<b>Efficiency</b>	80 PLUS Bronze (up to 85%)
<b>ATX (24 pin)</b>	1
<b>PCI-E 5.1 (16 pin)</b>	1 (450W)
<b>Fan Size</b>	120 mm
<b>EPS (4+4 pin)</b>	2
<b>Dimension</b>	140mm x 150mm x 86mm / 5.51 x 5.9 x 3.38 inches
<b>PCI-E (6+2 pin)</b>	3
<b>PFC Type</b>	Active PFC
<b>SATA (15 pin)</b>	3
<b>Protection</b>	OVP, OCP, SCP, OPP, UVP
<b>MOLEX (4 pin)</b>	2

### MAG A750BN PCIE5 III

AC INPUT	100-240V~, 10-5A, 50-60Hz			
DC OUTPUT	+5V	+3.3V	+12V	+5Vsb
	15A	15A	62.5A	2.5A
TOTAL POWER	100W		750W	12.5W
	750W			

### CONNECTOR



POWER - SUPPLY  
**MAG A750BN PCIE5 III**

YOUR POWER, RIGHT AWAY

CONNECTOR					
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL
1	2	1	3	3	2