



MAG A750BN PCIE5

- PCIe 5.0 Ready (300W)
- Ventola 120mm
- DC to DC power Design
- Progettazione PFC attiva
- Livelli di protezione industriale con OVP, OCP, SCP, OPP, OTP

SPECIFICATIONS

Modular	No
Input Voltage Range	100-240~
Fan Bearing	Sleeve Bearing
Power Watt	750W
Input Frequency	50~60Hz
Efficiency	80 PLUS Bronze (up to 85%)
ATX (24 pin)	1
Fan Size	120 mm
EPS (4+4 pin)	2
PCI-E 5.0 (16 pin)	1(300W)
Dimension	140mm x 150mm x 86mm / 5.51 x 5.9 x 3.38 inches
PCI-E (6+2 pin)	2
PFC Type	Active PFC
SATA (15 pin)	5
Protection	OCP, OVP, OPP, OTP, SCP
MOLEX (4 pin)	2
FDD (4 pin)	1

MAG A750BN PCIE5

AC INPUT	100-240V~, 10-5A, 50~60Hz				
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	20A	20A	62.5A	0.3A	2.5A
TOTAL POWER	120W	750W	3.6W	12.5W	
		750W			

CONNECTOR



POWER - SUPPLY

MAG A750BN PCIE5

YOUR POWER, RIGHT AWAY

CONNECTOR						
ATX	EPS	PCI-E 5.0	PCI-E	SATA	PERIPHERAL	FDD
1	2	1	2	5	2	1