



MAG A850GL PCIE5 WHITE

- Compatibile con ATX 3.1, cavo 16-pin bicolore PCIe 5.1 nativo
- Compatibile con le schede grafiche NVIDIA® GeForce RTX™ Serie 40
- Design completamente modulare, cavi piatti
- Certificazione 80 Plus Gold per alta efficienza
- Design con PFC attivo, protezioni di livello industriale: OVP, OCP, OPP, OTP, SCP, UVP
- Ventola da 120 mm con cuscinetto fluidodinamico (Fluid Dynamic Bearing)
- Topologia Full Bridge LLC con design a modulo DC-DC

SPECIFICATIONS

Model Name	TORX FAN 12CM
WEIGHT (CARD)	169g
Dimensions	120mm x 120mm x 25.6mm
Modular	Yes (full modular)
Input Voltage Range	100~240 VAC
Bearing Type	Hydro-Dynamic Bearing
Fan Bearing	Fluid Dynamic Bearing
Rated Speed	500 - 1800 ±15% RPM
Power Watt	850W
Power Excursion	1700W (*up to 200% of the PSU's rated power for 100µs)
Air Flow	19.79 - 71.27 CFM
Static Air Pressure	0.16 - 2.09 mm-H2O
Input Frequency	47-63Hz
Connector	4-Pin PWM/DC
Efficiency	80 PLUS Gold (up to 90%)
Life Expectancy	MTTF 150,000 Hours (25°C)
ATX (24 pin)	1
Fan Size	120 mm
EPS (4+4 pin)	2
PCI-E 5.0 (16 pin)	1 (600W)
Dimension	140 x 150 x 86 mm
PCI-E (6+2 pin)	4
PFC Type	Active PFC
SATA (15 pin)	8
Protection	OCP / OVP / OPP / OTP / SCP / UVP
MOLEX (4 pin)	4
FDD (4 pin)	1