



SPECIFICATIONS

Efficiency Rating	80 PLUS Platinum (up to 92%)
Modular	Yes (full modular)
Fan Size	135 mm
Fan Bearing	Fluid Dynamic Bearing
Dimensions (DxWxH)	150 x 150 x 86mm / 5.9 x 5.9 x 3.4 inches
PFC Type	Active PFC
Input Voltage	100-240V~
Power Watt	1000W
Input Frequency	50-60Hz
Protection	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO
ATX (24 pin)	1
EPS (8 pin)	1
EPS (4+4 PIN)	1
PCI-E (6+2 pin)	4
SATA (15 pin)	6
MOLEX (4 pin)	3
PCI-E 5.1 (16 pin)	1 (600W)

FEATURES



GPU SAFEGUARD

Featuring built-in overcurrent protection for the 12V-2x6 interface, the buzzer provides real-time warnings to alert users of any abnormalities.



FAN SAFEGUARD

The integrated fan failure protection immediately detects when the fan stops spinning. A buzzer will then sound, alerting you to the problem and preventing the power supply from overheating.



DUAL COLOR 12V-2x6 CONNECTOR

With its vibrant yellow connector, you can easily see if the cable is fully plugged in, which helps guarantee a secure connection.



OPTIMIZED THE SOUND LEVEL

This power supply is designed for quiet operation, delivering low noise levels like in the midnight, ensuring a serene computing experience free from disturbances.



EMBOSSED JACKET CABLE

The embossed cables are exceptionally flexible for easy routing and cable management, while also offering superior durability and a premium look.