



- イエローカラ 12V-2x6 ケーブル
- ATX 3.1 対応
- PCIe 5.1 対応 (450W)
- 80 PLUS Bronze
- 120mm Fan
- DC to DC コンバーター回路
- Active PFC 設計
- 保護回路機能 OVP, OCP, SCP, OPP, UVP

SPECIFICATIONS

Efficiency Rating	80 PLUS Bronze (up to 85%)
Modular	No
Fan Size	120 mm
Fan Bearing	Hydraulic Bearing
Dimensions (DxWxH)	140mm x 150mm x 86mm / 5.51 x 5.9 x 3.38 inches
PFC Type	Active PFC
Input Voltage	100-240V~
Power Watt	750W
Power Excursion	200%
Input Frequency	50-60Hz
Protection	OVP, OCP, SCP, OPP, UVP
ATX (24 pin)	1
EPS (4+4 PIN)	2
PCI-E (6+2 pin)	3
SATA (15 pin)	3
MOLEX (4 pin)	2
WEIGHT (CARD)	169g
Dimensions	120mm x 120mm x 25.6mm
Bearing Type	Hydro-Dynamic Bearing
Rated Speed	500 - 1800 ±15% RPM
Air Flow	19.79 - 71.27 CFM
Static Air Pressure	0.16 - 2.09 mm-H2O
Connector	4-Pin PWM/DC
PCI-E 5.1 (16 pin)	1 (450W)
Life Expectancy	MTTF 150,000 Hours (25°C)

MAG A750BN PCIE5 III

AC INPUT	100-240V~, 10-5A, 50-60Hz			
DC OUTPUT	+5V	+3.3V	+12V	+5Vsb
	15A	15A	62.5A	2.5A



POWER-SUPPLY

MAG A750BN PCIE5 III

YOUR POWER, RIGHT AWAY

MAG A750BN PCIE5 III

TOTAL POWER	100W	750W	12.5W
	750W		

CONNECTOR

ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL
1	2	1	3	3	2