MAG A750GL PCIE5

- ATX 3.0対応　ネイティブ16ピンコネクター対応
- NVIDIA® GeForce RTX™ 40 シリーズグラフィックスカード対応
- フルモジュラー設計、フラットケーブル採用
- 80 Plus Gold認証
- Active PFC設計, 産業レベルの保護回路 OVP,OCP,OPP,OTP, SCP,UVP
- 120mm FDBファン
- LLC FULL Bridge Topology with DC-DCモジュール設計
- 7年間の長期製品保証

SPECIFICATIONS

Efficiency Rating	80 PLUS Gold (up to 90%)
Modular	Yes (full modular)
Fan Size	120 mm
Fan Bearing	Fluid Dynamic Bearing
Dimensions (DxWxH)	140 x 150 x 86 mm
PFC Type	Active PFC
Input Voltage	100~240 VAC
Power Watt	750W
Power Excursion	1500W (*up to 200% of the PSU's rated power for 100μs)
Input Frequency	47-63Hz
Protection	OCP / OVP / OPP / OTP / SCP / UVP
ATX (24 pin)	1
EPS (4+4 PIN)	2
PCI-E 5.0 (16 pin)	1 (450W)
PCI-E (6+2 pin)	3
SATA (15 pin)	8
MOLEX (4 pin)	4
FDD (4 pin)	1

MAG A750GL PCIE5					
AC INPUT	100-240~, 10A , 47-63Hz				
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	20A	20A	62A	0.3A	2.5A
TOTAL POWER	110W		744W	3.6W	12.5W
	750W				

© 2023 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.

MAG A750GL PCIE5

CONNECTOR						
ATX (20+4 PIN)	EPS (4+4 PIN)	PCI-E5.0	PCI-E (6+2 PIN)	SATA	MOLEX (PERIPHERAL)	FDD
1	2	1	3	8	4	1

Generated 2023-07-27, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

© 2023 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.