



- Premium protection, GPU Safeguard+ and Fan Safeguard
- Server-grade materials, SiC interleaved PFC MOSFET
- Supports Nvidia® GeForce RTX™ 50 series graphics cards
- 2 x native 12V-2x6 connectors
- Dual-color 12V-2x6 cable
- 80 PLUS Titanium certified
- Optimized the sound level
- 100% all Server-grade 105°C capacitor
- Embossed Jacket Cables, the cables are more bending and routing
- Industrial level protection with OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO

## SPECIFICATIONS

<b>Modular</b>	Yes (full modular)
<b>Fan Bearing</b>	Fluid Dynamic Bearing
<b>Energía en vatios</b>	1600W
<b>Voltaje de entrada</b>	100-240V~
<b>Frecuencia de entrada</b>	50-60 Hz
<b>Eficiencia</b>	80 PLUS Titanium (up to 94%)
<b>ATX (24 pin)</b>	1
<b>PCI-E 5.1 (16 pin)</b>	2 (600W)
<b>Tamaño de ventilador</b>	135 mm
<b>EPS (4+4 pin)</b>	1
<b>Dimensiones</b>	190 x 150 x 86 mm
<b>PCI-E (6+2 pin)</b>	7
<b>Tipo de PFC</b>	Active PFC
<b>SATA (15 pin)</b>	8
<b>Protección</b>	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO
<b>MOLEX (4 pin)</b>	4

## MPG Ai1600TS PCIE5

AC INPUT	100-240V~, 15-10A, 50-60Hz			
DC OUTPUT	+5V	+3.3V	+12V	+5Vsb
	22A	22A	133.33A	3A
TOTAL POWER	120W		1599.96W	15W
	1600W			

## CONNECTOR

CONNECTOR					
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL
1	2	2	7	8	4