

SPECIFICATIONS

Rozmiar wentylatora	135 mm
Modularność	Yes (full modular)
Łożysko wiatraka	Fluid Dynamic Bearing
Skok mocy	1650W (*up to 220% of the PSU's rated power for 100µs)
Moc w watach	750W
Napięcie wejściowe	100-240V~
Częstotliwość wejściowa	50-60 Hz
Złącza ATX (24 pin)	1
Klasa efektywności	80 PLUS Gold (up to 90%)
Złącza PCI-E 5.1 (16 pin)	1 (450W)
Złącza EPS (4+4 pin)	2
Złącza PCI-E (6+2 pin)	4
Wymiary (DxWxH)	150 x 150 x 86 mm
Złącza SATA (15 pin)	5
Typ PFC	Active PFC
Złącza MOLEX (4 pin)	2
Zabezpieczenia	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO
FDD (4 pin)	1

FEATURES



Vertical GPU Mount Support

Can support vertical mounting of graphics card depending on the users' preference.



Front USB 3.2 Gen 2x2 Type C

Synergize with a compatible MSI motherboard through bridging with a USB 3.2 Gen 2x2 Type-C port for convenient access.




EK Distribution Plate Support

Designed in partner with EK, the gaming cases can fit an EK distribution plate inside.



ARGB Fan

Packed with premium quality system fans to cool your system for the maximum performance



Optimized Air Flow

Up to 10x system fans could be installed. Provides the whole system with ventilation for better stability



Touch Panel

The touch panel can display a wide range of system information and graphics.