

SPECIFICATIONS

КПД	80 PLUS Titanium (до 94%)
Модульность	Полностью модульный
Размер вентилятора	135 мм
Подшипник вентилятора	Гидродинамический подшипник
Тип PFC	Active PFC
Входное напряжение	100-240В~
Мощность	1600Вт
Входная частота	50-60 Гц
Защита	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO
ATX (24 pin)	1
EPS (4+4 pin)	1
PCI-E 5.1 (16 pin)	2 (600Вт)
PCI-E (6+2 pin)	7
SATA (15 pin)	8
MOLEX (4 pin)	4
Размеры	190 x 150 x 86 мм

FEATURES



GPU SAFEGUARD+

Built-in overcurrent protection specific to the 12V-2x6 interface. The MSI CENTER software issues a real-time warning prompting the user to inspect the connection of the 12V-2x6.




FAN SAFEGUARD

The integrated fan failure protection immediately detects when the fan stops spinning. A buzzer will then sound, alerting you to the problem and preventing the power supply from overheating.



EMBOSSED JACKET CABLE

The embossed cables are exceptionally flexible for easy routing and cable management, while also offering superior durability and a premium look.



DUAL COLOR 12V-2x6 CONNECTOR

With its vibrant yellow connector, you can easily see if the cable is fully plugged in, which helps guarantee a secure connection.



SiC MOSFET

The server-grade materials, not only enhance power supply's stability, also reduce losses, and optimize heat dissipation.



OPTIMIZED THE SOUND LEVEL

This power supply is designed for quiet operation, delivering low noise levels like in the midnight, ensuring a serene computing experience free from disturbances.