



- Supports Nvidia® GeForce RTX™ 50 series graphics cards
- 2 x native 12V-2x6 connector
- Dual-color 12V-2x6 cable
- 80 PLUS Gold certified
- Optimized the sound level
- 100% all Server-grade 105°C capacitor
- Embossed Jacket Cables, the cables are more bending and routing
- Industrial level protection with OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO

## SPECIFICATIONS

<b>Modular</b>	Yes (full modular)
<b>Fan Bearing</b>	Fluid Dynamic Bearing
<b>Power Excursion</b>	2350W (*up to 235% of the PSU's rated power for 100µs)
<b>Power Watt</b>	1000W
<b>Input Voltage</b>	100-240V~
<b>Input Frequency</b>	50-60 Hz
<b>Efficiency Rating</b>	80 PLUS Gold (up to 90%)
<b>ATX (24 pin)</b>	1
<b>EPS (8 pin)</b>	2
<b>PCI-E 5.1 (16 pin)</b>	2 (600W)
<b>Fan Size</b>	135 mm
<b>Dimension</b>	150 x 150 x 86 mm
<b>PCI-E (6+2 pin)</b>	1
<b>PFC Type</b>	Active PFC
<b>SATA (15 pin)</b>	8
<b>Protection</b>	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO
<b>MOLEX (4 pin)</b>	4

### MPG A1000GS PCIE5

AC INPUT	100-240~, 13A, 50-60Hz				
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	22A	22A	83.3A	0.3A	3A
TOTAL POWER	120W	999.6W	3.6W	15W	
	1000W				

### CONNECTOR

<b>CONNECTOR</b>					
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL
1	2	2	1	8	4