POWER SUPPLY

MAG A1000PLS PCIE5

SPECIFICATIONS

Modular	Yes (full modular)
Fan Bearing	Fluid Dynamic Bearing
Power Watt	1000W
Input Voltage	100-240V~
ATX (24 pin)	1
Input Frequency	50-60Hz
EPS (8 pin)	1
Efficiency	80 PLUS Platinum (up to 92%)
PCI-E 5.1 (16 pin)	1 (600W)
EPS (4+4 pin)	1
Fan Size	135 mm
PCI-E (6+2 pin)	4
Dimension	150 x 150 x 86mm / 5.9 x 5.9 x 3.4 inches
SATA (15 pin)	6
PFC Type	Active PFC
MOLEX (4 pin)	3
Protection	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO

FEATURES

GPU SAFEGUARD

Featuring built-in overcurrent protection for the 12V-2x6 interface, the buzzer provides real-time warnings to alert users of any abnormalities.

FAN SAFEGUARD

The integrated fan failure protection immediately detects when the fan stops spinning. A buzzer will then sound, alerting you to the problem and preventing the power supply from overheating.

DUAL COLOR 12V-2x6 CONNECTOR

With its vibrant yellow connector, you can easily see if the cable is fully plugged in, which helps guarantee a secure connection.

OPTIMIZED THE SOUND LEVEL

This power supply is designed for quiet operation, delivering low noise levels like in the midnight, ensuring a serene computing experience free from disturbances.

EMBOSSED JACKET CABLE

The embossed cables are exceptionally flexible for easy routing and cable management, while also offering superior durability and a premium look.

Generated 2026-03-23, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

© 2026 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.