

## SPECIFICATIONS

<b>Modular</b>	Yes (full modular)
<b>Fan Bearing</b>	Fluid Dynamic Bearing
<b>Power Watt</b>	1300W
<b>Input Voltage</b>	100-240V~
<b>ATX (24 pin)</b>	1
<b>Input Frequency</b>	50-60 Hz
<b>Efficiency</b>	80 PLUS Titanium (up to 94%)
<b>PCI-E 5.1 (16 pin)</b>	2 (600W)
<b>EPS (4+4 pin)</b>	1
<b>Fan Size</b>	135 mm
<b>PCI-E (6+2 pin)</b>	7
<b>Dimension</b>	190 x 150 x 86 mm
<b>SATA (15 pin)</b>	8
<b>PFC Type</b>	Active PFC
<b>MOLEX (4 pin)</b>	4
<b>Protection</b>	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO

## FEATURES



### GPU SAFEGUARD+

Built-in overcurrent protection specific to the 12V-2x6 interface. The MSI CENTER software issues a real-time warning prompting the user to inspect the connection of the 12V-2x6.




### SiC MOSFET

The server-grade materials, not only enhance power supply's stability, also reduce losses, and optimize heat dissipation.



### FAN SAFEGUARD

The integrated fan failure protection immediately detects when the fan stops spinning. A buzzer will then sound, alerting you to the problem and preventing the power supply from overheating.



### DUAL COLOR 12V-2x6 CONNECTOR

With its vibrant yellow connector, you can easily see if the cable is fully plugged in, which helps guarantee a secure connection.



### OPTIMIZED THE SOUND LEVEL

This power supply is designed for quiet operation, delivering low noise levels like in the midnight, ensuring a serene computing experience free from disturbances.



### EMBOSSED JACKET CABLE

The embossed cables are exceptionally flexible for easy routing and cable management, while also offering superior durability and a premium look.