



- 12V-2x6 雙色線
- 相容 ATX 3.1
- 相容 PCIe 5.1(300W)
- 850 PLUS 銅牌認證
- 120 mm風扇
- DC to DC 供電設計
- 主動式 PFC 設計e 5
- 工業水準的保護機制，包含 OVP□OCP□SCP□OPP□ UVP

SPECIFICATIONS

WEIGHT (CARD)	169g
Efficiency Rating	80 PLUS Bronze (up to 85%)
Modular	No
Fan Size	120 mm
Fan Bearing	Hydrualic Bearing
Dimensions (DxWxH)	140mm x 150mm x 86mm / 5.51 x 5.9 x 3.38 inches
PFC Type	Active PFC
Input Voltage Range	100-240V~
Power Watt	650W
Power Excursion	200%
Input Frequency Range	50-60Hz
Protection	OVP, OCP, SCP, OPP, UVP
Dimensions	120mm x 120mm x 25.6mm
ATX (24 pin)	1
EPS (4+4 pin)	2
PCI-E (6+2 pin)	2
Air Flow	19.79 - 71.27 CFM
SATA (15 pin)	3
Static Air Pressure	0.16 - 2.09 mm-H2O
MOLEX (4 pin)	2
Connector	4-Pin PWM/DC
PCI-E 5.1 (16 pin)	1 (300W)

MAG A650BN PCIE5 III

AC INPUT	100-240V~, 10-5A, 50-60Hz			
DC OUTPUT	+5V	+3.3V	+12V	+5Vsb
	15A	15A	54A	2.5A
TOTAL POWER	100W		648W	12.5W
	650W			



POWER - SUPPLY

MAG A650BN PCIE5 III

YOUR POWER, RIGHT AWAY

CONNECTOR					
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL
1	2	1	2	3	2