



## SPECIFICATIONS

|                       |                                                                                                                                           |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Efficiency Rating     | 80 PLUS TITANIUM                                                                                                                          |
| Power Watt            | 1600W                                                                                                                                     |
| Modular               | Fully Modular                                                                                                                             |
| Form Factor           | ATX                                                                                                                                       |
| Dimensions (DxWxH)    | 190x150x86 mm                                                                                                                             |
| PFC Type              | Active PFC                                                                                                                                |
| Input Voltage Range   | 100~240 VAC                                                                                                                               |
| Input Frequency Range | 50~60 Hz                                                                                                                                  |
| Fan                   | Size: 135mm<br>Bearing: Two-Ball                                                                                                          |
| Protection            | OVP / OCP / OTP / OPP / SCP / UVP / SIP / NLO                                                                                             |
| Connector             | 1 x Motherboard (24 pin)<br>2 x CPU (4+4 pin)<br>2 x PCIe 5 (12+4 pin) / 600W<br>9 x PCIe (6+2 pin)<br>8 x SATA<br>8 x Peripheral (4 pin) |

## FEATURES



### ATX 3.1 READY

Compliant with Intel Intel PSDG (Power Supply Design Guide) ATX 3.1.



### BRAIDED CABLE

Tightly braided and built to last, it resists heavy tension and pulling to prevent internal wire damage.



### DUAL 12V-2x6 CONNECTORS

It comes with dual 12V-2x6 connectors, making it ready to support high-end graphics cards in the future



### OPTIMIZED THE SOUND LEVEL

This power supply is designed for quiet operation, delivering low noise levels like in the midnight, ensuring a serene computing experience free from disturbances.



### DUAL COLOR 12V-2x6 CONNECTOR

With its vibrant yellow connector, you can easily see if the cable is fully plugged in, which helps guarantee a secure connection.



### SiC MOSFET

The server-grade materials, not only enhance power supply's stability, also reduce losses, and optimize heat dissipation.