



- Supports Nvidia® GeForce RTX™ 50 series graphics cards
- Native 12V-2x6 connector
- Dual-color 12V-2x6 cable
- 80 PLUS Gold certified
- Optimized the sound level
- Main 105°C capacitor
- Embossed Jacket Cables, the cables are more bending and routing
- Industrial level protection with OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO

## SPECIFICATIONS

<b>Efficiency Rating</b>	80 PLUS Gold (up to 90%)
<b>Modular</b>	Yes (full modular)
<b>Fan Bearing</b>	Fluid Dynamic Bearing
<b>Power Watt</b>	650W
<b>Power Excursion</b>	1430W (*up to 220% of the PSU's rated power for 100µs)
<b>Input Voltage</b>	100-240V~
<b>Input Frequency Range</b>	50-60 Hz
<b>ATX (24 pin)</b>	1
<b>EPS (4+4 pin)</b>	2
<b>PCI-E 5.1 (16 pin)</b>	1 (300W)
<b>Fan Size</b>	135 mm
<b>Dimension</b>	150 x 150 x 86 mm
<b>PCI-E (6+2 pin)</b>	2
<b>PFC Type</b>	Active PFC
<b>SATA (15 pin)</b>	5
<b>Protection</b>	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO
<b>MOLEX (4 pin)</b>	2
<b>FDD (4 pin)</b>	1

### MAG A650GLS PCIE5

AC INPUT	100-240V~, 5-10A, 50-60Hz				
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	18A	18A	54A	0.3A	2.5A
TOTAL POWER	100W	648W	3.6W	12.5W	
	650W				

CONNECTOR						
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL	FDD
1	2	1	2	5	2	1