


## SPECIFICATIONS

<b>Efficiency Rating</b>	80 PLUS Gold (up to 90%)
<b>Modular</b>	Yes (full modular)
<b>Fan Bearing</b>	Fluid Dynamic Bearing
<b>Power Excursion</b>	1650W (*up to 220% of the PSU's rated power for 100µs)
<b>Power Watt</b>	750W
<b>Input Frequency Range</b>	50-60 Hz
<b>Input Voltage</b>	100-240V~
<b>ATX (24 pin)</b>	1
<b>PCI-E 5.1 (16 pin)</b>	1 (450W)
<b>EPS (4+4 pin)</b>	2
<b>Fan Size</b>	135 mm
<b>PCI-E (6+2 pin)</b>	4
<b>Dimensions (DxWxH)</b>	150 x 150 x 86 mm
<b>SATA (15 pin)</b>	5
<b>PFC Type</b>	Active PFC
<b>MOLEX (4 pin)</b>	2
<b>Protection</b>	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO
<b>FDD (4 pin)</b>	1

## FEATURES



### DUAL COLOR 12V-2x6 CONNECTOR

With its vibrant yellow connector, you can easily see if the cable is fully plugged in, which helps guarantee a secure connection.



### EMBOSSED JACKET CABLE

The embossed cables are exceptionally flexible for easy routing and cable management, while also offering superior durability and a premium look.



### +12V Single Rail

The power supply delivers stable output currents under heavy graphics card loading.