



- Dual-color 12V-2x6 Cable
- ATX 3.1 Ready
- PCIe 5.1 Ready (600W)
- 105°C Main Electrolytic Capacitor
- 80 PLUS Platinum Certification
- Embossed Jacket Certified Cables
- Industrial level protection with OCP, OTP, OPP, SCP, OVP, UVP, SIP, NLO

SPECIFICATIONS

Efficiency Rating	80 PLUS Platinum (up to 92%)
Modular	Fully Modular
Fan Bearing	Hydraulic Bearing
Power Watt	850W
Power Excursion	200%
Input Voltage	100-240V~
Input Frequency Range	50-60Hz
ATX (24 pin)	1
EPS (4+4 pin)	2
PCI-E 5.1 (16 pin)	1 (600W)
Fan Size	120 mm
Dimensions (DxWxH)	150 x 150 x 86 mm / 5.9 x 5.9 x 3.38 inches
PCI-E (6+2 pin)	3
PFC Type	Active PFC
SATA (15 pin)	6
Protection	OCP, OTP, OPP, SCP, OVP, UVP, SIP, NLO
MOLEX (4 pin)	2

PRO A850PL PCIE5

AC INPUT	100-240V~, 12-6.3A, 50-60Hz				
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	20A	20A	70.8A	0.3A	2.5A
TOTAL POWER	100W	849.6W	3.6W	12.5W	
	850W				

CONNECTOR



POWER - SUPPLY

PRO A850PL PCIE5

YOUR POWER, RIGHT AWAY

CONNECTOR					
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL
1	2	1	3	6	2