



- Supports Nvidia® GeForce RTX™ 50 series graphics cards
- Native 12V-2x6 connector
- Dual-color 12V-2x6 cable
- 80 PLUS Gold certified
- Optimized the sound level
- Main 105°C capacitor
- Embossed Jacket Cables, the cables are more bending and routing
- Industrial level protection with OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO

SPECIFICATIONS

Dimensions	120mm x 120mm x 25.6mm
Modular	Yes (full modular)
Fan Bearing	Fluid Dynamic Bearing
Power Watt	1000W
Input Voltage Range	100-240V~
Power Excursion	2200W (*up to 220% of the PSU's rated power for 100µs)
Input Frequency	47-63 Hz
ATX (24 pin)	1
Efficiency Rating	80 PLUS Gold (up to 90%)
EPS (8 pin)	2
PCI-E 5.1 (16 pin)	1 (600W)
Fan Size	135 mm
Dimensions (DxWxH)	150 x 150 x 86 mm
PCI-E (6+2 pin)	4
PFC Type	Active PFC
SATA (15 pin)	11
Protection	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO
MOLEX (4 pin)	4
FDD (4 pin)	1

MAG A1000GLS PCIE5

AC INPUT	100-240V~, 12A, 47-63Hz				
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	20A	20A	83.3A	0.3A	3A
TOTAL POWER	100W	999.6W	3.6W	15W	
	1000W				



POWER - SUPPLY

MAG A1000GLS PCIE5

CONNECTOR						
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL	FDD
1	2	1	4	11	4	1