



- Dual-color 12V-2x6 Cable
- ATX 3.1 Ready
- PCIe 5.1 Ready (600W)
- 80 PLUS Gold
- 120mm Fan
- DC to DC power Design
- Half bridge LLC resonant Design
- Taiwanese branded-capacitors
- Industrial level protection with OVP, OCP, SCP, OPP, UVP

SPECIFICATIONS

Modular	Non Modular
Fan Bearing	Hydraulic Bearing
Power Watt	850W
Input Voltage Range	100-240V~
Input Frequency	47-63Hz
Efficiency Rating	80 PLUS Gold (up to 90%)
Fan Size	120 mm
Dimensions (DxWxH)	140 x 150 x 86 mm / 5.51 x 5.9 x 3.38 inches
PFC Type	Active PFC
Protection	OCP, OVP, OPP, OTP, SCP, UVP

MAG GN85A					
AC INPUT	100-240V~, 12.0A, 47-63Hz				
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	20A	20A	70.8A	0.3A	3A
TOTAL POWER	100W	550W	3.6W	15W	
	850W				

CONNECTOR					
ATX	EPS	PCI-E 5.1	PCI-E	SATA	PERIPHERAL
1	2	1	3	4	2