

MAG A500DN



- Quạt 120mm
- Bảo vệ chuẩn công nghiệp
OCP,OVP,OPP,OTP, SCP,UVP
- Thiết kế Active PFC
- Trang bị cáp đẹp

SPECIFICATIONS

Modular	No
Fan Bearing	Hydro Bearing
Power Watt	500W
Input Voltage	110-240~
Input Frequency	50~60Hz
Efficiency	80 PLUS Standard (up to 80%)
Life Expectancy	MTTF 150,000 Hours (25°C)
ATX (24 pin)	1
Fan Size	120 mm
EPS (4+4 pin)	1
Dimension	150mm x 140mm x 86mm / 5.91 x 5.51 x 3.39 inches
PCI-E (6+2 pin)	2
SATA (15 pin)	5
PFC Type	Active PFC
MOLEX (4 pin)	2
Protection	OCP, OVP, OPP, SCP
FDD (4 pin)	1

MAG A500DN						
AC INPUT	110-240V~, 8.0A , 50~60Hz					
DC OUTPUT	+5V	+3.3V	+12V1	+12V2	-12V	+5Vsb
	14A	14A	21A	21A	0.3A	2.5A
TOTAL POWER	105W		456W		3.6W	12.5W
	500W					



POWER-SUPPLY

MAG A500DN

YOUR POWER, RIGHT AWAY

CONNECTOR						
ATX (20+4 PIN)	EPS (4+4 PIN)	PCI-E5.0	PCI-E (6+2 PIN)	SATA	MOLEX (PERIPHERAL)	FDD
1	1		2	5	2	1