



SPECIFICATIONS

Taille de la dalle	23,6"
Taille de pixel (H X V)	0,272 (H) x 0,272 (V)
Jacks audio	1 x sortie audio
Compatibilité VESA	100 x 100 mm
Dimensions du carton (L x H x P)	600 x 164 x 411 mm
CERTIFICATS	Energy Star 8.0
Taux de rafraîchissement	100 Hz
Compatibilité	PC, Mac, PS5™, PS4™, Xbox, smartphone, ordinateur portable * Toutes les marques déposées et les marques enregistrées citées ici appartiennent à leur propriétaire respectif.
Zone d'affichage active (mm)	521 (H) x 293 (V)
Temps de réponse	4 ms (GTG Min.) / 1 ms MPRT
Type de dalle	VA
Angle de vision	178° (H) / 178° (V)
Ratio	16:9
Courbure	1500R
Remarques	HDMI™ : 1920 x 1080 (jusqu'à 100 Hz) DP : 1920 x 1080 (jusqu'à 100 Hz) Support Adaptive-Sync
sRGB	110 % (CIE 1976)
Dimensions	537 x 237 x 407 mm
Entrée alimentation	100~240 V, 50~60 Hz
Type d'alimentation	Interne
Contraste	3000:1
Résolution	1920 x 1080 (Full HD)
Affichage des couleurs	16,7 millions de teintes
Profondeur des couleurs	8 bits

FEATURES



Quadruple M.2 Connectors

Onboard 4x M.2 connectors with one Lightning Gen 5 solution for the maximum storage performance.




Magnetic M.2 Shield Frozr

This patent magnetic design enables true "wire-less" RGB function, enhances the installation process and maximizes the storage performance.



Touch Panel

The touch panel can display a wide range of system information and graphics.



Optimized Air Flow

Up to 10x system fans could be installed. Provides the whole system with ventilation for better stability



ARGB Fan

Packed with premium quality system fans to cool your system for the maximum performance



Wave Curved 3.0

Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.

CONNECTIONS



1. 1x DC Jack
2. 1x DP (1.2a)
3. 1x HDMI™ (1.4b)
4. 1x Headphone-out
5. 1x Kensington Lock
6. OSD Button