



SPECIFICATIONS

Signal Frequency	72~216 KHz(H) / 48-144 Hz(V)
BRIGHTNESS (NITS)	300 cd/m2
ADOBE RGB / DCI-P3 / SRGB	87% / 93% / 121% (CIE1976)
HDR SUPPORT	HDR Ready
USB Ports	2x USB 5Gbps Type-A 1x USB 5Gbps Type-B
AUDIO PORTS	1x Headphone-out
SPEAKER	3W x2
DYNAMIC REFRESH RATE TECHNOLOGY	AMD FreeSync™ Technology
Dimension with Stand (W x D x H)	613.49 x 200.81 x 401.72 mm (24.15 x 7.91 x 15.82 inch)
ADJUSTMENT (SWIVEL)	-30° ~ 30°
Dimension without Stand (W x D x H)	613.49 x 63.81 x 362.45 mm (24.15 x 2.51 x 14.27 inch)
ADJUSTMENT (HEIGHT)	0 ~ 110 mm
CARTON DIMENSION (W X D X H)	613.49 x 63.81 x 362.45 mm (24.15 x 2.51 x 14.27 inch)
ADJUSTMENT (PIVOT)	-90° ~ 90°
ACCESSORIES	1x HDMI Cable (2.0b), 1x Type-C Cable (3.2 Gen 1), 1x USB Type-B to A Cable (3.2 Gen 1), 1x Power Cord, 1x Quick Guide, 4x VESA Wall Mount Screw, Color Report
PANEL SIZE	27"
PANEL RESOLUTION	2560 x 1440 (WQHD)
REFRESH RATE	144Hz
RESPONSE TIME	1ms (MPRT) / 4ms (GTG)
PANEL TYPE	IPS
POWER INPUT	100~240V, 50/60Hz
VIEWING ANGLE	178°(H) / 178°(V)
ASPECT RATIO	16:9
CONTRAST RATIO	1500:1
ACTIVE DISPLAY AREA (MM)	597.736(H) x 335.664(V)
PIXEL PITCH (H X V)	0.2331(H) x 0.2331(V)
SURFACE TREATMENT	Anti-glare
DISPLAY COLORS	16.7M
COLOR BIT	8 bits (6 bits + FRC)

FEATURES



IPS Panel with Wide Viewing Angle

Instantly optimize the screen colors and brightness to ensure that you enjoy every detail at its best.



EyesErgo

An eye care solution designed with ergonomics in mind. Includes Eye care & Ergonomic features.



Circular Polarization

Converts harsh digital rays into soft, naturally-polarized light to prevent eye strain and maximize visual comfort.



144Hz Game Ready

Thanks to the high refresh rate and adaptive-sync support, our gaming experience becomes completely smooth and free from interruptions.



Type C 65W Power Delivery

Built-in an USB Type-C connection with 65W power delivery allows you to effortlessly connect to and charge your devices



Delta-E (ΔE) ≤ 2

Factory pre-calibrated to guarantee a truly expressive hues and color accuracy.




PRO MAX 271QPHW E14

BE YOUR WINDOW TO THE WORLD

VIDEO PORTS	2x HDMI™ 2.0b (WQHD@144Hz) 1x DisplayPort 1.2a 1x Type-C (DP alt.) w/ 65W PD
KENSINGTON LOCK	Yes
VESA MOUNTING	75 x 75 mm
POWER TYPE	Internal Power Board
ADJUSTMENT (TILT)	-5° ~ 20°
WEIGHT (NW / GW)	6.4 kg (14.11 lbs) / 10.1 kg (22.27 lbs)
NOTE	HDMI™: 2560 x 1440 (Up to 144Hz) DisplayPort: 2560 x 1440 (Up to 144Hz) Type-C: 2560 x 1440 (Up to 144Hz) Delta-E (ΔE) ≤ 2 Support: HDMI CEC/ MSI Power Link, KVM 1.0, FW Update, PI App, M-Mate App; Non-Support: PIP/PBP

CONNECTIONS



- 1. 5-Way Navi-Key
- 2. 1x Headphone-out
- 3. 2x HDMI™ 2.0b (FHD@144Hz)
- 4. 1x DisplayPort 1.2a
- 5. 1x Type-C (DP alt.) w/ 65W PD
- 6. 1x USB 5Gbps Type-B
- 7. 2x USB 5Gbps Type-A
- 8. AC-in
- 9. Kensington-Lock