

BUSINESS PRODUCTIVITY MONITOR **PRO MP271C**

BE YOUR WINDOW TO THE WORLD







SPECIFICATIONS

民首ロナ	27"
屏幕尺寸 小踏束	
分辨率	1920 x 1080 (Full HD)
刷新率	75Hz
响应时间	1ms (MPRT) / 5ms (GTG)
面板类型	VA
亮度 (nits)	250 cd/m2
比例	16:9
曲率	1500R
对比度	4000:1
显示区域 (mm)	597.888(H) X 336.312(V)
表面处理	Anti-glare
发色数	16.7M
视频接口	1x HDMI™ (1.4b) 1x D-Sub (VGA)
音频接口	1x Headphone-out
Kensington锁	Yes
VESA支架	100 x 100 mm
电源类型	Internal Power
电源输入	100~240V, 50~60Hz
色阶	8 bits
扬声器	2x 2W
俯仰调节	-3.5° ~ 21.5°
包装 (W x H x D)	610.34 x 237 x 454.8 mm (24.03 x 9.33 x 17.91 inch)
包装尺寸 (W X H X D)	684 x 156 x 474 mm (26.93 x 6.14 x 18.66 inch)
音频接口	1x Headphone-out
兼容性	PC, Mac, PS5 [™] , PS4 [™] , Xbox, Mobile, Notebook * All trademarks and the registered trademarks are the property of their respective owners.
扬声器	2x 2W
Compatibility	PC, Mac, PS5 [™] , PS4 [™] , Xbox, Mobile, Notebook * All trademarks and the registered trademarks are the property of their respective owners.
VESA MOUNTING	100 x 100 mm
备注	HDMI™: 1920 x 1080 (Up to 75Hz) D-Sub: 1920 x 1080 (Up to 60Hz)

FEATURES



Anti-Flicker technology

MSI Anti-Flicker technology provides a very comfortable viewing experience by reducing the amount of screen flicker.

Less Blue Light

Effectively reduce blue light which could cause serious long-term damage to your eyes.

Display Kit Support

Providing the most convenient tool, the proper color & display mode to you while working with it everyday.

Built-In Speaker

Built-in speakers allow you to listen clearly without connecting external speakers.

VESA Mountable

To be mounted on the wall of your office & home with a VESA standard design which can make it completely invisible on a desk.



BUSINESS PRODUCTIVITY MONITOR

PRO MP271C

BE YOUR WINDOW TO THE WORLD

PANEL SIZE	27"
PANEL RESOLUTION	1920 x 1080 (FHD)
CARTON DIMENSION (W X H X D)	684 x 156 x 474 mm (26.93 x 6.14 x 18.66 inch)
WEIGHT (NW / GW)	5.4 kg (11.9 lbs) / 7.3 kg (16.09 lbs)
NOTE	HDMI [™] : 1920 x 1080 (Up to 75Hz) D-Sub: 1920 x 1080 (Up to 60Hz)
ADJUSTMENT (TILT)	-3.5° ~ 21.5°
POWER INPUT	100~240V, 50~60Hz
POWER TYPE	Internal Power
RESPONSE TIME	1ms (MPRT) / 5ms (GTG)
KENSINGTON LOCK	Yes
VIDEO PORTS	1x HDMI™ (1.4b) 1x D-Sub (VGA)
COLOR BIT	8 bits
DISPLAY COLORS	16.7M
SURFACE TREATMENT	Anti-glare
PIXEL PITCH (H X V)	0.3114(H) X 0.3114(V)
ACTIVE DISPLAY AREA (MM)	597.888(H) X 336.312(V)
sRGB	97.7% (CIE 1976)
CONTRAST RATIO	4000:1
CURVATURE	Curved 1500R
ASPECT RATIO	16:9
VIEWING ANGLE	178°(H) / 178°(V)
BRIGHTNESS (NITS)	250 cd/m2
PANEL TYPE	VA
REFRESH RATE	75Hz

CONNECTIONS



- 1. 1x HDMI[™] (1.4b)
- 2. 1x D-Sub (VGA)
- 3. 1x Headphone-out
 4. 1x Kensington Lock
- 5. 5x OSD Button