



SPECIFICATIONS

BRIGHTNESS (NITS)	300 cd/m2
DCR	100000000:1
Signal Frequency	52.85~158.54 KHz(H) / 48~144 Hz(V)
ADOBE RGB / DCI-P3 / SRGB	85% / 84% / 107% (CIE1976)
HDR SUPPORT	HDR Ready
SURFACE TREATMENT	Anti-glare
Webcam	N/A
AUDIO PORTS	1x Line-in 1x Headphone-out
Activated Range	48~144Hz
Reproduktory	2W x2
POWER TYPE	Internal Power Board
POWER INPUT	100~240V, 50/60Hz
DYNAMIC REFRESH RATE TECHNOLOGY	Adaptive-Sync
Dimension with Stand (W x D x H)	539.36 x 226.93 x 519.29 mm (21.23 x 8.93 x 20.44 inch)
Dimension without Stand (W x D x H)	539.36 x 51.71 x 314.67 mm (21.23 x 2.04 x 12.39 inch)
CARTON DIMENSION (W X D X H)	600 x 125 x 500 mm (23.62 x 4.92 x 19.69 inch)
Nastavení (výška)	0~130 mm
Nastavení pivot	-90°~90°
CERTIFICATES	CB/CE Energy Star
ADJUSTMENT (SWIVEL)	-45°~45°
ACCESSORIES	1x HDMI™ Cable (1.4), 1x Power Cord (C13), 1x Quick Guide, 4x Stand Screw, 1x VESA Plate, 4x VESA Plate Screw
Velikost panelu	23.8"
PANEL RESOLUTION	1920 x 1080 (FHD)
Obnovovací frekvence	144Hz
Doba odezvy	1ms (MPRT) / 4ms (GTG)
PANEL TYPE	IPS
Úhel pohledu	178°(H) / 178°(V)
Poměr stran	16:9
Kontrastní poměr	1500:1
ACTIVE DISPLAY AREA (MM)	527.04(H) x 296.46(V)

FEATURES



EZ PCIe Release

A simple press of a button to effortlessly lock or unlock the PCIe slot, simplifying the installation and removal of the graphics card.

Rozteč pixelů (H x V)	0.2745(H) x 0.2745(V)
Počet barev	16.7M, 8 bits (6 bits + FRC)
VIDEO PORTS	1x HDMI™ 2.0 (FHD@144Hz) 1x DisplayPort 1.2a 1x D-Sub (VGA)
KENSINGTON LOCK	Yes
CURVATURE	Flat
Montáž VESA	100 x 100 mm
Nastavení náklonu	-5° ~ 20°
WEIGHT (NW / GW)	5.25 kg (11.57 lbs) / 7.51 kg (16.56 lbs)
NOTE	HDMI™: 1920 x 1080 (Up to 144Hz) DisplayPort: 1920 x 1080 (Up to 144Hz) D-Sub (VGA): (Up to 60Hz) Support: HDMI™ CEC/ MSI Power Link; Non Support: KVM, PIP/PBP

CONNECTIONS



1. 5-way Navigator
2. AC-in
3. 1x DisplayPort 1.4a
4. 1x HDMI™ 2.0 (FHD@144Hz)
5. 1x D-Sub (VGA)
6. 1x Line-in
7. 1x Headphone-out
8. Kensington Lock