



SPECIFICATIONS

Signal Frequency	30~270 KHz(H) / 40~120 Hz(V)
ADOBE RGB / DCI-P3 / SRGB	97.5% / 99% / 138.2% (CIE1976)
PANEL SIZE	26.5"
PANEL RESOLUTION	3840 x 2160 (UHD)
VIEWING ANGLE	178°(H) / 178°(V)
REFRESH RATE	120Hz
RESPONSE TIME	0.03ms (GtG)
PANEL TYPE	QD-OLED
ASPECT RATIO	16:9
CURVATURE	Flat
HDR SUPPORT	VESA DisplayHDR True Black 400
CONTRAST RATIO	1500000 : 1
ACTIVE DISPLAY AREA (MM)	589.97(H) x 332.93(V)
PIXEL PITCH (H X V)	0.153(H) x 0.153(V)
SURFACE TREATMENT	Anti-Glare Low Reflection
Audio Interface	1x Headphone-out
DISPLAY COLORS	1.07B
COLOR BIT	10 bits
VIDEO PORTS	2x HDMI™ 2.1 (UHD@120Hz) 1x DisplayPort 1.4a 1x Type-C (DP alt.) w/ 15W PD
KENSINGTON LOCK	Yes
VESA MOUNTING	100 x 100 mm
SPEAKER	2x 2.5W
BRIGHTNESS (NITS)	SDR: 250 HDR: 1000
POWER TYPE	Internal Power Board
POWER INPUT	100~240V, 50/60Hz
DYNAMIC REFRESH RATE TECHNOLOGY	NVIDIA G-SYNC Compatible AMD FreeSync™ Premium Pro
Dimension with Stand (W x D x H)	611.1 x 200.6 x 560.3 mm (24.06 x 7.90 x 22.06 inch)
ADJUSTMENT (TILT)	-5° ~ 20°
Dimension without Stand (W x D x H)	611.1 x 73.0 x 356.3 mm (24.06 x 2.87 x 14.03 inch)
ADJUSTMENT (SWIVEL)	-30° ~ 30°
ADJUSTMENT (PIVOT)	-90° ~ 90°
CARTON DIMENSION (W X D X H)	770 x 142 x 478 mm (30.31 x 5.59 x 18.82 inch)

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



4K 120Hz

4K clarity at 120Hz. Everything you see is sharper, and every movement is remarkably fluid.



Tandem OLED

The QD-OLED Penta Tandem™ panel integrates a 5-layer light-emitting structure to boost light efficiency by up to 30%.



VisiClarity

VisiClarity masterfully integrates Anti-Glare Low Reflection technology to eliminate distracting light, providing a window of pure, undisturbed depth.



DarkArmor Film

Delivers 40% deeper blacks and a 2.5x more scratch-resistant screen surface.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



0.03ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 0.03ms GtG response time.



PIP/PBP Technology

Display and view dual contents simultaneously with multi-screen functionality.

ADJUSTMENT (HEIGHT)	0 ~ 150 mm
WEIGHT (NW / GW)	6.6 kg (14.55 lbs) / 9.5 kg (20.94 lbs)
ACCESSORIES	1x DisplayPort Cable (1.4a), 1x Power Cord (C13), 1x Quick Guide, 1x VESA Plate, 4x VESA Plate Screw, VESA Adapter Kit, Color Report, 1x Fiber Cloth, 1x Cable Clip
Note	HDMI™ : 3840 x 2160 (Up to 120Hz) DisplayPort: 3840 x 2160 (Up to 120Hz) Type-C: 3840 x 2160 (Up to 120Hz) Delta-E (ΔE) ≤ 2 Support: HDMI™ CEC/ MSI Power Link, OLED Care 2.0, FW Update, PIP/PBP Non-Support: KVM 1.0

CONNECTIONS



- 1. Headphone-out
- 2. 2x HDMI™ 2.1 (UHD@120Hz)
- 3. DisplayPort 1.4a
- 4. Type-C (DP alt.) w/ 15W PD
- 5. Kensington Lock
- 6. AC-in