



SPECIFICATIONS

Signal Frequency	30~270 KHz(H) / 40~120 Hz(V)
Resolución de la pantalla	3840 x 2160 (UHD)
Tasa de refresco	120Hz
ADOBE RGB / DCI-P3 / SRGB	97.5% / 99% / 138.2% (CIE1976)
HDR SUPPORT	VESA DisplayHDR True Black 400
Audio Interface	1x Headphone-out
KENSINGTON LOCK	Yes
SPEAKER	2x 2.5W
Brillo (Nits)	SDR: 250 HDR: 1000
TECNOLOGÍA DE FRECUENCIA DE ACTUALIZACIÓN DINÁMICA	NVIDIA G-SYNC Compatible AMD FreeSync™ Premium Pro
Dimension with Stand (W x D x H)	611.1 x 200.6 x 560.3 mm (24.06 x 7.90 x 22.06 inch)
Regulable (inclinación)	-5° ~ 20°
Dimension without Stand (W x D x H)	611.1 x 73.0 x 356.3 mm (24.06 x 2.87 x 14.03 inch)
CARTON DIMENSION (W X D X H)	770 x 142 x 478 mm (30.31 x 5.59 x 18.82 inch)
ADJUSTMENT (HEIGHT)	0 ~ 150 mm
ADJUSTMENT (PIVOT)	-90° ~ 90°
ACCESSORIES	1x DisplayPort Cable (1.4a), 1x Power Cord (C13), 1x Quick Guide, 1x VESA Plate, 4x VESA Plate Screw, VESA Adapter Kit, Color Report, 1x Fiber Cloth, 1x Cable Clip
ADJUSTMENT (SWIVEL)	-30° ~ 30°
Tamaño del panel	26.5"
Tiempo de respuesta	0.03ms (GtG)
Tipo de panel	QD-OLED
Ángulo de visión	178°(H) / 178°(V)
Relación de aspecto	16:9
Curvo	Flat
Relación de contraste	1500000 : 1
Puertos de video	2x HDMI™ 2.1 (UHD@120Hz) 1x DisplayPort 1.4a 1x Type-C (DP alt.) w/ 15W PD
Tratamiento de la superficie	Anti-Glare Low Reflection
Colores de pantalla	1.07B
Bit de color	10 bits

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



4K 120Hz

4K clarity at 120Hz. Everything you see is sharper, and every movement is remarkably fluid.



Tandem OLED

The QD-OLED Penta Tandem™ panel integrates a 5-layer light-emitting structure to boost light efficiency by up to 30%.



VisiClarity

VisiClarity masterfully integrates Anti-Glare Low Reflection technology to eliminate distracting light, providing a window of pure, undisturbed depth.



DarkArmor Film

Delivers 40% deeper blacks and a 2.5x more scratch-resistant screen surface.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



0.03ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 0.03ms GtG response time.



PIP/PBP Technology

Display and view dual contents simultaneously with multi-screen functionality.

Obeservación	HDMI™: 3840 x 2160 (Up to 120Hz)
	DisplayPort: 3840 x 2160 (Up to 120Hz)
	Type-C: 3840 x 2160 (Up to 120Hz)
	Delta-E (ΔE) ≤ 2
	Support: HDMI™ CEC/ MSI Power Link, OLED Care 2.0, FW Update, PIP/PBP Non-Support: KVM 1.0
Peso (NW / GW)	6.6 kg (14.55 lbs) / 9.5 kg (20.94 lbs)
Entrada de alimentación	100~240V, 50/60Hz
Tipo de alimentación	Internal Power Board
SopORTE VESA	100 x 100 mm
Área de visualización activa (mm)	589.97(H) x 332.93(V)
Tamaño de píxel (H x V)	0.153(H) x 0.153(V)

CONNECTIONS



1. Headphone-out
2. 2x HDMI™ 2.1 (UHD@120Hz)
3. DisplayPort 1.4a
4. Type-C (DP alt.) w/ 15W PD
5. Kensington Lock
6. AC-in