



SPECIFICATIONS

PANEL RESOLUTION	1920 x 1080 (FHD)
REFRESH RATE	75Hz
sRGB	114.44% (CIE 1976)
AUDIO PORTS	1x Headphone-out
KENSINGTON LOCK	Yes
SPEAKER	2x 2W
ADJUSTMENT (TILT)	-3.5° ~ 21.5°
Compatibility	PC, Mac, PS5™, PS4™, Xbox, Mobile, Notebook * All trademarks and the registered trademarks are the property of their respective owners.
PANEL TYPE	VA
POWER INPUT	100~240V, 50~60Hz
CARTON DIMENSION (W X H X D)	600 x 164 x 411 mm (23.62 x 6.46 x 16.18 inch)
WEIGHT (NW / GW)	4.1kg / 5.6kg
NOTE	HDMI™: 1920 x 1080 (Up to 75Hz) DP: 1920 x 1080 (Up to 75Hz)
DIMENSION (W X H X D)	536.9 x 237 x 407.4 mm (21.14 x 9.33 x 16.04 inch)
VESA MOUNTING	100 x 100 mm
BRIGHTNESS (NITS)	250 cd/m2
POWER TYPE	Internal Power
PANEL SIZE	23.6"
VIDEO PORTS	1x HDMI™ (1.4b) 1x DP (1.2a)
COLOR BIT	8 bits
DISPLAY COLORS	16.7M
SURFACE TREATMENT	Anti-glare
PIXEL PITCH (H X V)	0.27156(H) x 0.27156(V)
RESPONSE TIME	4ms (GTG Min.) / 1ms MPRT
CONTRAST RATIO	3000:1
CURVATURE	1500R
ASPECT RATIO	16:9
VIEWING ANGLE	178°(H) / 178°(V)
ACTIVE DISPLAY AREA (MM)	521.3952(H) x 293.2848(V)


FEATURES



Premium Thermal Design

Heavy plated heatsink with heat-pipe / high quality 7W/mK MOSFET thermal pads / extra choke thermal pads / onboard M.2 Shield Frozr.

CONNECTIONS



1. 1x DP (1.2a)
2. 1x HDMI™ (1.4b)
3. 1x Headphone-out
4. 1x Kensington Lock
5. 5x OSD Button