



SPECIFICATIONS

| | |
|---|--|
| DCR | 100000000:1 |
| Signal Frequency | 70.6~176.4 KHz(H) / 48~120 Hz(V) |
| Resolución de la pantalla | 3440 x 1440 (UWQHD) |
| Tasa de refresco | 120Hz |
| ADOBE RGB / DCI-P3 / SRGB | 89% / 91% / 114% (CIE 1976) |
| HDR SUPPORT | HDR Ready |
| USB Ports | N/A |
| Audio Interface | 1x Headphone-out |
| Webcam | N/A |
| KENSINGTON LOCK | Yes |
| Activated Range | 48~120Hz |
| SPEAKER | 2W x2 |
| Brillo (Nits) | 300 cd/m ² |
| TECNOLOGÍA DE FRECUENCIA DE ACTUALIZACIÓN DINÁMICA | Adaptive-Sync |
| Regulable (inclinación) | -3.5° ~ 21.5° |
| Dimension with Stand (W x D x H) | 809.34 x 237 x 469.54 mm (31.86 x 9.33 x 18.49 inch) |
| Dimension without Stand (W x D x H) | 809.34 x 106.79 x 365.84 mm (31.86 x 4.20 x 14.40 inch) |
| CARTON DIMENSION (W X D X H) | 985 x 198 x 490 mm (38.78 x 7.80 x 19.29 inch) |
| ADJUSTMENT (HEIGHT) | N/A |
| ADJUSTMENT (PIVOT) | N/A |
| Certificados | CB/CE Energy Star |
| ADJUSTMENT (SWIVEL) | N/A |
| Compatibilidad | PC, Mac, PS5™, PS4™, Xbox, Mobile, Notebook * All trademarks and the registered trademarks are the property of their respective owners. |
| ACCESSORIES | 1x DP Cable (1.4a), 1x Quick Guide, 4x Stand Screw, 1x Power Cord (C13) |
| Tamaño del panel | 34" |
| Tiempo de respuesta | 1ms (MPRT) / 4ms (GtG) |
| Tipo de panel | VA |
| Entrada de alimentación | 100~240V, 50/60Hz |
| Ángulo de visión | 178°(H) / 178°(V) |
| Relación de aspecto | 21:9 |

FEATURES



Premium Thermal Design

Heavy plated heatsink with heat-pipe / high quality 7W/mK MOSFET thermal pads / extra choke thermal pads / onboard M.2 Shield Frozr.

| | |
|--|---|
| Relación de contraste | 3500:1 |
| Área de visualización activa (mm) | 797.22(H) x 333.72(V) |
| Tamaño de píxel (H x V) | 0.23175(H) x 0.23175(V) |
| Tratamiento de la superficie | Anti-glare |
| Colores de pantalla | 1.07B, 10bits (8bits + FRC) |
| Puertos de vídeo | 2x HDMI™ 2.0b (UWQHD@100Hz) 1x DisplayPort 1.4a (HBR2) |
| Curvo | Curve 1500R |
| Soporte VESA | 100 x 100 mm |
| Tipo de alimentación | Internal Power Board |
| Peso (NW / GW) | 7.1 kg (15.65 lbs) / 11.1 kg (24.47 lbs) |
| Obeservación | HDMI™: 3440 x 1440 (Up to 100Hz) DisplayPort: 3440 x 1440 (Up to 120Hz) Support: HDMI™ CEC/ MSI Power Link, PIP/PBP, FW Update ; Non Support: KVM 1.0 |

CONNECTIONS



1. OSD Buttons
2. AC-in
3. 2x HDMI™ 2.0b (UWQHD@100Hz)
4. 1x DisplayPort 1.4a
5. Headphone-out
6. Kensington Lock