BUSINESS PRODUCTIVITY MONITOR

PRO MP341CQPHG E12

BUSINESS & PRODUCTIVITY MONITOR





SPECIFICATIONS

DCR	100000000:1
Signal Frequency	70.6~176.4 KHz(H) / 48~120 Hz(V)
Resolución de la pantalla	3440 x 1440 (UWQHD)
Tasa de refresco	120Hz
ADOBE RGB / DCI-P3 / SRGB	89% / 91% / 114% (CIE 1976)
HDR SUPPORT	HDR Ready
USB Ports	N/A
Audio Interface	1x Headphone-out
Webcam	N/A
KENSINGTON LOCK	Yes
Activated Range	48~120Hz
SPEAKER	2W x2
Brillo (Nits)	300 cd/m²
TECNOLOGÍA DE FRECUENCIA DE ACTUALIZACIÓN DINÁMICA	AMD FreeSync™ Premium
Regulable (inclinación)	-3.5° ~ 21.5°
Dimension with Stand (W x D x H)	809.34 x 237 x 469.54 mm (31.86 x 9.33 x 18.49 inch)
Dimension without Stand (W x D x H)	809.34 x 106.79 x 365.84 mm (31.86 x 4.20 x 14.40 inch
CARTON DIMENSION (W X D X H)	985 x 198 x 490 mm (38.78 x 7.80 x 19.29 inch)
ADJUSTMENT (HEIGHT)	N/A
ADJUSTMENT (PIVOT)	N/A
Certificados	CB/CE Energy Star
ADJUSTMENT (SWIVEL)	N/A
Compatibilidad	PC, Mac, PS5™, PS4™, Xbox, Mobile, Notebook * All trademarks and the registered trademarks are the property of their respective owners.
ACCESSORIES	1x DP Cable (1.4a), 1x Quick Guide, 4x Stand Screw, 1x Power Cord (C13)
Tamaño del panel	34"
Tiempo de respuesta	1ms (MPRT) / 4ms (GtG)
Tipo de panel	VA
Entrada de alimentación	100~240V, 50/60Hz
Ángulo de visión	178°(H) / 178°(V)
Relación de aspecto	21:9

FEATURES

Premium Thermal Design

Heavy plated heatsink with heat-pipe / high quality 7W/mK MOSFET thermal pads / extra choke thermal pads / onboard M.2 Shield Frozr.

© 2026 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.

PRO MP341CQPHG E12

BUSINESS & PRODUCTIVITY MONITOR

Relación de contraste	3500:1
Área de visualización activa (mm)	797.22(H) x 333.72(V)
Tamaño de píxel (H x V)	0.23175(H) x 0.23175(V)
Tratamiento de la superficie	Anti-glare
Colores de pantalla	1.07B, 10bits (8bits + FRC)
Puertos de video	2x HDMI™ 2.0b (UWQHD@100Hz) 1x DisplayPort 1.4a (HBR2)
Curvo	Curve 1500R
Soporte VESA	100 x 100 mm
Tipo de alimentación	Internal Power Board
Peso (NW / GW)	7.1 kg (15.65 lbs) / 11.1 kg (24.47 lbs)
Obeservación	HDMI™: 3440 x 1440 (Up to 100Hz) DisplayPort: 3440 x 1440 (Up to 120Hz) Support: HDMI™ CEC/ MSI Power Link, PIP/PBP, FW Update ; Non Support: KVM 1.0

CONNECTIONS



1. OSD Buttons
2. AC-in
3. 2x HDMI™ 2.0b (UWQHD@100Hz)
4. 1x DisplayPort 1.4a
5. Headphone-out
6. Kensington Lock

Generated 2026-11-09, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

© 2026 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.