



SPECIFICATIONS

| | |
|--|--|
| PANEL SIZE | 26.5" |
| PANEL RESOLUTION | 3840 x 2160 (UHD) |
| REFRESH RATE | 120Hz |
| RESPONSE TIME | 0.03ms (GtG) |
| PANEL TYPE | QD-OLED |
| BRIGHTNESS (NITS) | SDR: 250 HDR: 1000 |
| VIEWING ANGLE | 178°(H) / 178°(V) |
| ASPECT RATIO | 16:9 |
| CURVATURE | Flat |
| CONTRAST RATIO | 1500000 : 1 |
| Signal Frequency | 30~270 KHz(H) / 40~120 Hz(V) |
| ADOBE RGB / DCI-P3 / SRGB | 97.5% / 99% / 138.2% (CIE1976) |
| ACTIVE DISPLAY AREA (MM) | 589.97(H) x 332.93(V) |
| PIXEL PITCH (H X V) | 0.153(H) x 0.153(V) |
| SURFACE TREATMENT | Anti-Glare Low Reflection |
| DISPLAY COLORS | 1.07B |
| COLOR BIT | 10 bits |
| HDR SUPPORT | VESA DisplayHDR True Black 400 |
| VIDEO PORTS | 2x HDMI™ 2.1 (UHD@120Hz) 1x DisplayPort 1.4a 1x Type-C (DP alt.) w/ 15W PD |
| Audio Interface | 1x Headphone-out |
| KENSINGTON LOCK | Yes |
| SPEAKER | 2x 2.5W |
| VESA MOUNTING | 100 x 100 mm |
| POWER TYPE | Internal Power Board |
| POWER INPUT | 100~240V, 50/60Hz |
| DYNAMIC REFRESH RATE TECHNOLOGY | AMD FreeSync™ Premium Pro Technology |
| ADJUSTMENT (TILT) | -5° ~ 20° |
| ADJUSTMENT (SWIVEL) | -30° ~ 30° |
| ADJUSTMENT (PIVOT) | -90° ~ 90° |
| ADJUSTMENT (HEIGHT) | 0 ~ 150 mm |
| Dimension with Stand (W x D x H) | 611.1 x 200.6 x 560.3 mm (24.06 x 7.90 x 22.06 inch) |
| Dimension without Stand (W x D x H) | 611.1 x 73.0 x 356.3 mm (24.06 x 2.87 x 14.03 inch) |

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



4K 120Hz

4K clarity at 120Hz. Everything you see is sharper, and every movement is remarkably fluid.



Tandem OLED

The QD-OLED Penta Tandem™ panel integrates a 5-layer light-emitting structure to boost light efficiency by up to 30%.



VisiClarity

VisiClarity masterfully integrates Anti-Glare Low Reflection technology to eliminate distracting light, providing a window of pure, undisturbed depth.



DarkArmor Film

Delivers 40% deeper blacks and a 2.5x more scratch-resistant screen surface.



OLED Care 2.0

MSI has developed a more advanced version to provide several care services and significantly reduce the chances of OLED screen aging.



0.03ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 0.03ms GtG response time.



PIP/PBP Technology

Display and view dual contents simultaneously with multi-screen functionality.

| | |
|-------------------------------------|---|
| CARTON DIMENSION (W X D X H) | 770 x 142 x 478 mm (30.31 x 5.59 x 18.82 inch) |
| WEIGHT (NW / GW) | 6.6 kg (14.55 lbs) / 9.5 kg (20.94 lbs) |
| ACCESSORIES | 1x DisplayPort Cable (1.4a), 1x Power Cord (C13), 1x Quick Guide, 1x VESA Plate, 4x VESA Plate Screw, VESA Adapter Kit, Color Report, 1x Fiber Cloth, 1x Cable Clip |
| Note | HDMI™: 3840 x 2160 (Up to 120Hz) DisplayPort: 3840 x 2160 (Up to 120Hz) Type-C: 3840 x 2160 (Up to 120Hz) Delta-E (ΔE) ≤ 2 Support: HDMI™ CEC/ MSI Power Link, OLED Care 2.0, FW Update, PIP/PBP Non-Support: KVM 1.0 |

CONNECTIONS



1. Headphone-out
2. 2x HDMI™ 2.1 (UHD@120Hz)
3. DisplayPort 1.4a
4. Type-C (DP alt.) w/ 15W PD
5. Kensington Lock
6. AC-in