



SPECIFICATIONS

PANEL SIZE	34"
PANEL RESOLUTION	3440 x 1440 (UWQHD)
REFRESH RATE	144Hz
RESPONSE TIME	0.03ms (GtG)
PANEL TYPE	QD-OLED
BRIGHTNESS (NITS)	SDR: 300 HDR: 1300
VIEWING ANGLE	178°(H) / 178°(V)
ASPECT RATIO	21:9
CURVATURE	Flat
CONTRAST RATIO	1500000 : 1
Signal Frequency	237.2~239 KHz(H) / 48~144 Hz(V)
ADOBE RGB / DCI-P3 / SRGB	97.4% / 99% / 136.4% (CIE1976)
ACTIVE DISPLAY AREA (MM)	800.06(H) x 337.06(V)
PIXEL PITCH (H X V)	0.2315(H) x 0.2315(V)
SURFACE TREATMENT	Anti-Glare Low Reflection
DISPLAY COLORS	1.07B
COLOR BIT	10 bits
HDR SUPPORT	VESA DisplayHDR True Black 500
VIDEO PORTS	2x HDMI™ 2.1 (FRL 12G) (UWQHD@144Hz) 1x DisplayPort 1.4a (HBR3) 1x Type-C (DP alt.) w/ 98W PD 1x Type-C (DP alt.) w/ 15W PD
USB Ports	4x USB 5Gbps Type-A 1x USB 5Gbps Type-B
Audio Interface	1x Headphone-out
KENSINGTON LOCK	Yes
SPEAKER	2x 3W
VESA MOUNTING	100 x 100 mm
POWER TYPE	Internal Power Board
POWER INPUT	100~240V, 50/60Hz
DYNAMIC REFRESH RATE TECHNOLOGY	Adaptive-Sync
ADJUSTMENT (TILT)	-5° ~ 20°
ADJUSTMENT (SWIVEL)	-30° ~ 30°
ADJUSTMENT (PIVOT)	-10° ~ 10°
ADJUSTMENT (HEIGHT)	0 ~ 130 mm

FEATURES



QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



5th-gen QD-OLED

The 5th-gen Tandem QD-OLED pixel arrangement utilizes the RGB Stripe layout, fundamentally elevating display quality. This design minimizes color fringing and significantly enhances the clarity of text.



DarkArmor Film

Delivers 40% deeper blacks and a 2.5x more scratch-resistant screen surface.



AI Care Sensor

AI Care integrates AI sensors to dynamically optimize OLED protection based on real-time usage, making the system even smarter.



VisiClarity

VisiClarity masterfully integrates Anti-Glare Low Reflection technology to eliminate distracting light, providing a window of pure, undisturbed depth.




Dual Type-C 98W/ 15W PD

Built-in an USB Type-C connection with 98W power delivery allows you to effortlessly connect to and charge your devices.

Dimension with Stand (W x D x H)	817.9 x 200.6 x 549.2 mm (32.20 x 7.90 x 21.62 inch)
Dimension without Stand (W x D x H)	817.9 x 73.7 x 373.4 mm (32.20 x 2.90 x 14.70 inch)
CARTON DIMENSION (W X D X H)	985 x 169 x 475 mm (38.78 x 6.65 x 18.70 inch)
WEIGHT (NW / GW)	8.6 kg (18.96 lbs) / 13.5 kg (29.76 lbs)
ACCESSORIES	1x HDMI™ Cable (2.1), 1x DisplayPort Cable (1.4a), 1x Type-C Cable (3.2 Gen 1), 1x USB Type-B to A Cable (3.2 Gen 1), 1x Power Cord, 1x Quick Guide, 4x VESA Wall Mount Screw, 1x VESA Plate, 4x VESA Plate Screw, 1x VESA Adaptor Kit, 1x Cable Clip, 1x Fiber Cloth, Color Report
Note	HDMI™: 3440 x 1440 (Up to 144Hz) DisplayPort: 3440 x 1440 (Up to 144Hz) Type-C: 3440 x 1440 (Up to 144Hz) Delta-E (ΔE) ≤ 2 Support: HDMI CEC/ MSI Power Link, OLED Care 3.0, KVM 2.0, FW Update, PIP/PBP Pass EPEAT Silver by country

CONNECTIONS



- 1. Kensington Lock
- 2. AC-in
- 3. 2x HDMI™ 2.1 (FRL 12G) (UWQHD@144Hz)
- 4. 1x DisplayPort 1.4a (HBR3)
- 5. 1x Type-C (DP alt.) w/ 98W PD
- 6. 1x Type-C (DP alt.) w/ 15W PD
- 7. 1x USB 5Gbps Type-B
- 8. 4x USB 5Gbps Type-A
- 9. 1x Headphone-out