



SPECIFICATIONS

面板尺寸	34"
最佳解析度	3440 x 1440 (UWQHD)
更新頻率	120Hz
反應時間	1ms (MPRT) / 4ms (GtG)
面板類型	VA
亮度	300 cd/m ²
可視角度	178°(H) / 178°(V)
螢幕比例	21:9
曲面螢幕	1500R
靜態對比度	3500:1
顯示區域(MM)	797.22 (H) x 333.72 (V)
像素 (H X V)	0.23175 (H) x 0.23175 (V)
表面處理	Anti-Glare
色彩顯示	1.07B
COLOR BIT	10 bits (8bits + FRC)
影像連接埠	2x HDMI™ 2.0b (UWQHD@100Hz) 1x DisplayPort 1.4a 1x Type-C (DP Alt.) w/ 98W PD
音頻接孔	1 x Headphone-out
USB接孔	1x USB 5Gbps Type-B 2x USB 5Gbps Type-A
ADOBE RGB / DCI-P3 / SRGB	92% / 95% / 119%
肯辛頓鎖孔	Yes
SPEAKER	2x 3W
VESA安裝	75 x 75 mm
電源規格	External Adaptor 19V 9.47A
HDR SUPPORT	HDR Ready
電源輸入	100~240V, 50~60Hz
調整 (仰角)	-5° ~ 20°
調整 (左右旋轉)	-30° ~ 30°
調整 (垂直旋轉)	-5° ~ 5°
調整 (高度)	0 ~ 110 mm
動態刷新率技術	Adaptive-Sync
尺寸 (寬X高X深)	808.6 x 424.1 x 250.6 mm (31.83 x 16.70 x 9.87 inch)
紙箱尺寸 (寬 X 高 X 深)	945 x 510 x 245 mm (37.2 x 20.1 x 9.7 inch)
重量	8.05 kg (17.81 lbs) / 11.9 kg (26.23 lbs)

FEATURES

UWQHD (3440 x 1440)

3440 X 1440

Game titles will even look better, displaying more details due to the WQHD (3440 x 1440) resolution.

120Hz High Refresh Rate

120Hz

Enjoy the high-quality entertainment with a smoother and flicker-free images.



Type C Display

Allows you to connect the latest devices more conveniently and with less trouble.



KVM Function Support

Control multiple devices via one set of keyboard, mouse, and MSI monitor.



PIP / PBP Mode

PIP/PBP mode provide a better efficiency for creators when need it



EyesErgo

An eye care solution designed with ergonomics in mind.



Built-In Speaker

Built-in speakers allow you to listen clearly without connecting external speakers.

PC, Mac, PS5™, PS4™, Xbox, Mobile,
Notebook

*All trademarks and the registered
trademarks are the property of their
respective owners.

影像輸出兼容性

CB/CE, Energy Star

認證**ACCESSORIES**

1x DisplayPort 1.2a cable, 1x USB 3.2 Gen 1
Type-B to A cable, 1x Power Adaptor, 1x
Power Cord, 1x Quick Guide, 4x VESA Wall
Mount Screws

備註

HDMI™: 3440 x 1440 (Up to 100Hz)
DisplayPort: 3440 x 1440 (Up to 120Hz)
Type-C: 3440 x 1440 (Up to 120Hz)
HDMI™ CEC Support
Adobe RGB, DCI-P3 and sRGB follow CIE1976
Standard

CONNECTIONS

1. 1x DC Jack
2. 1x Headphone-out
3. 2x HDMI 2.0b
4. 1x DisplayPort 1.4a
5. 1x Type-C (DP Alt.) w/ 98W PD
6. 1x USB 5Gbps Type-B
7. 2x USB 5Gbps Type-A
8. 1x Kensington Lock
9. OSD Button