



## SPECIFICATIONS

Signal Frequency	54~169.78 KHz(H) / 48~144 Hz(V)
ADOBE RGB / DCI-P3 / SRGB	93% / 96% / 122% (CIE1976)
SURFACE TREATMENT	Anti-Glare with Circular Polarization
HDR SUPPORT	HDR Ready
USB Ports	2x USB 5Gbps Type-A 1x USB 5Gbps Type-B
AUDIO PORTS	1x Headphone-out
BRIGHTNESS (NITS)	300 cd/m2
SPEAKER	2x 3W
DYNAMIC REFRESH RATE TECHNOLOGY	AMD FreeSync™ Technology
Dimension with Stand (W x D x H)	541.93 x 200.81 x 381.11mm (21.34 x 7.91 x 15.00 inch)
Dimension without Stand (W x D x H)	541.93 x 65.44 x 322.28 mm (21.34 x 2.58 x 12.69 inch)
CARTON DIMENSION (W X D X H)	814 x 149 x 410 mm (32.05 x 5.87 x 16.14 inch)
ADJUSTMENT (HEIGHT)	0 ~ 110 mm
ADJUSTMENT (PIVOT)	-90° ~ 90°
ADJUSTMENT (SWIVEL)	-30° ~ 30°
ACCESSORIES	1x HDMI™ Cable (2.0b), 1x Type-C Cable (3.2 Gen 1), 1x USB Type-B to A Cable (3.2 Gen 1), 1x Power Cord, 1x Quick Guide, 4x VESA Wall Mount Screw, Color Report, 1x Cable Clip
PANEL SIZE	23.8"
PANEL RESOLUTION	1920 x 1080 (FHD)
REFRESH RATE	144Hz
RESPONSE TIME	1ms (MPRT) / 4ms (GTG)
PANEL TYPE	IPS
POWER INPUT	100~240V, 50/60Hz
VIEWING ANGLE	178°(H) / 178°(V)
ASPECT RATIO	16:9
CONTRAST RATIO	1500:1
ACTIVE DISPLAY AREA (MM)	527.04(H) x 296.46(V)
PIXEL PITCH (H X V)	0.2745(H) x 0.2745(V)
DISPLAY COLORS	16.7M
COLOR BIT	8 bits (6 bits + FRC)

## FEATURES



### IPS Panel with Wide Viewing Angle

Instantly optimize the screen colors and brightness to ensure that you enjoy every detail at its best.



### EyesErgo

An eye care solution designed with ergonomics in mind. Includes Eye care & Ergonomic features.



### Circular Polarization

Converts harsh digital rays into soft, naturally-polarized light to prevent eye strain and maximize visual comfort.



### 144Hz Game Ready

Thanks to the high refresh rate and adaptive-sync support, our gaming experience becomes completely smooth and free from interruptions.



### Type C 65W Power Delivery

Built-in a USB Type-C connection with 65W power delivery allows you to effortlessly connect to and charge your devices




### Delta-E (ΔE) ≤ 2

Factory pre-calibrated to guarantee a truly expressive hues and color accuracy.

<b>VIDEO PORTS</b>	1x HDMI™ 2.0b (FHD@144Hz) 1x DisplayPort 1.2a 1x Type-C (DP alt.) w/ 65W PD
<b>KENSINGTON LOCK</b>	Yes
<b>VESA MOUNTING</b>	75 x 75 mm
<b>POWER TYPE</b>	Internal Power Board
<b>ADJUSTMENT (TILT)</b>	-5° ~ 20°
<b>WEIGHT (NW / GW)</b>	5.35 kg (11.79 lbs) / 8 kg (17.64 lbs)
<b>NOTE</b>	HDMI™: 1920 x 1080 (Up to 144Hz) DisplayPort: 1920 x 1080 (Up to 144Hz) Type-C: 1920 x 1080 (Up to 144Hz) Delta-E (ΔE) ≤ 2 Support: HDMI™ CEC / MSI Power Link, KVM 1.0, FW Update; Non-Support: PIP/PBP

## CONNECTIONS



1. 5-Way Navi-Key
2. 1x USB 5Gbps Type-B
3. 2x USB 5Gbps Type-A
4. 1x Type-C (DP alt.) w/ 65W PD
5. 1x DisplayPort 1.2a
6. 1x HDMI™ 2.0b (FHD@144Hz)
7. 1x Headphone-out
8. AC-in
9. Kensington-Lock