



SPECIFICATIONS

| | |
|-------------------------------------|--|
| Signal Frequency | 72~216 KHz(H) / 48-144 Hz(V) |
| ADOBE RGB / DCI-P3 / SRGB | 87% / 93% / 121% (CIE1976) |
| HDR SUPPORT | HDR Ready |
| COLOR BIT | 8 bits (6 bits + FRC) |
| USB Ports | 2x USB 5Gbps Type-A 1x USB 5Gbps Type-B |
| AUDIO PORTS | 1x Headphone-out |
| SPEAKER | 3W x2 |
| BRIGHTNESS (NITS) | 300 cd/m2 |
| DYNAMIC REFRESH RATE TECHNOLOGY | Adaptive-Sync |
| Dimension with Stand (W x D x H) | 613.49 x 200.81 x 401.72 mm (24.15 x 7.91 x 15.82 inch) |
| Dimension without Stand (W x D x H) | 613.49 x 63.81 x 362.45 mm (24.15 x 2.51 x 14.27 inch) |
| CARTON DIMENSION (W X D X H) | 613.49 x 63.81 x 362.45 mm (24.15 x 2.51 x 14.27 inch) |
| ADJUSTMENT (HEIGHT) | 0 ~ 110 mm |
| ADJUSTMENT (PIVOT) | -90° ~ 90° |
| ADJUSTMENT (SWIVEL) | -30° ~ 30° |
| ACCESSORIES | 1x HDMI Cable (2.0b), 1x Type-C Cable (3.2 Gen 1), 1x USB Type-B to A Cable (3.2 Gen 1), 1x Power Cord, 1x Quick Guide, 4x VESA Wall Mount Screw, Color Report |
| PANEL SIZE | 27" |
| PANEL RESOLUTION | 2560 x 1440 (WQHD) |
| REFRESH RATE | 144Hz |
| RESPONSE TIME | 1ms (MPRT) / 4ms (GTG) |
| PANEL TYPE | IPS |
| POWER INPUT | 100~240V, 50/60Hz |
| VIEWING ANGLE | 178°(H) / 178°(V) |
| ASPECT RATIO | 16:9 |
| CONTRAST RATIO | 1500:1 |
| ACTIVE DISPLAY AREA (MM) | 597.736(H) x 335.664(V) |
| PIXEL PITCH (H X V) | 0.2331(H) x 0.2331(V) |
| SURFACE TREATMENT | Anti-glare |
| DISPLAY COLORS | 16.7M |

FEATURES



IPS Panel with Wide Viewing Angle

Instantly optimize the screen colors and brightness to ensure that you enjoy every detail at its best.



EyesErgo

An eye care solution designed with ergonomics in mind. Includes Eye care & Ergonomic features.



Circular Polarization

Converts harsh digital rays into soft, naturally-polarized light to prevent eye strain and maximize visual comfort.



144Hz Game Ready

Thanks to the high refresh rate and adaptive-sync support, our gaming experience becomes completely smooth and free from interruptions.



Type C 65W Power Delivery

Built-in a USB Type-C connection with 65W power delivery allows you to effortlessly connect to and charge your devices




Delta-E (ΔE) ≤ 2

Factory pre-calibrated to guarantee a truly expressive hues and color accuracy.

| | |
|--------------------------|---|
| VIDEO PORTS | 2x HDMI™ 2.0b (WQHD@144Hz) 1x DisplayPort 1.2a 1x Type-C (DP alt.) w/ 65W PD |
| KENSINGTON LOCK | Yes |
| VESA MOUNTING | 75 x 75 mm |
| POWER TYPE | Internal Power Board |
| ADJUSTMENT (TILT) | -5° ~ 20° |
| WEIGHT (NW / GW) | 6.4 kg (14.11 lbs) / 10.1 kg (22.27 lbs) |
| NOTE | HDMI™: 2560 x 1440 (Up to 144Hz) DisplayPort: 2560 x 1440 (Up to 144Hz) Type-C: 2560 x 1440 (Up to 144Hz) Delta-E (ΔE) ≤ 2 Support: HDMI CEC/ MSI Power Link, KVM 1.0, FW Update, PI App, M-Mate App; Non-Support: PIP/PBP |

CONNECTIONS



1. 5-Way Navi-Key
2. 1x Headphone-out
3. 2x HDMI™ 2.0b (FHD@144Hz)
4. 1x DisplayPort 1.2a
5. 1x Type-C (DP alt.) w/ 65W PD
6. 1x USB 5Gbps Type-B
7. 2x USB 5Gbps Type-A
8. AC-in
9. Kensington-Lock