



SPECIFICATIONS

Częstotliwość sygnału	54~169.78 KHz(H) / 48~144 Hz(V)
Jasność (Nity)	300 cd/m ²
Czas reakcji	1ms (MPRT) / 4ms (GTG)
ADOBE RGB / DCI-P3 / SRGB	93% / 96% / 122% (CIE1976)
Wsparcie HDR	HDR Ready
Porty USB	2x USB 5Gbps Type-A 1x USB 5Gbps Type-B
PORTY AUDIO	1x Headphone-out
Głośnik	2x 3W
TECHNOLOGIA DYNAMIC REFRESH RATE	Adaptive-Sync
Wymiary z podstawą (szer. x głęb. x wys.)	541.93 x 200.81 x 381.11mm (21.34 x 7.91 x 15.00 inch)
Wymiary bez podstawy (szer. x głęb. x wys.)	541.93 x 65.44 x 322.28 mm (21.34 x 2.58 x 12.69 inch)
WYMIARY OPAKOWANIA (SZER. X GŁĘB. X WYS.)	814 x 149 x 410 mm (32.05 x 5.87 x 16.14 inch)
Regulacja (wysokość)	0 ~ 110 mm
Regulacja (obrót pionowy)	-90° ~ 90°
Regulacja (obrót poziomy)	-30° ~ 30°
Akcesoria	1x HDMI™ Cable (2.0b), 1x Type-C Cable (3.2 Gen 1), 1x USB Type-B to A Cable (3.2 Gen 1), 1x Power Cord, 1x Quick Guide, 4x VESA Wall Mount Screw, Color Report, 1x Cable Clip
Rozmiar matrycy	23.8"
Rozdzielczość	1920 x 1080 (FHD)
Odświeżanie	144Hz
Typ panelu	IPS
Moc wejściowa	100~240V, 50/60Hz
Kąt widzenia	178°(H) / 178°(V)
Proporcje obrazu	16:9
Kontrast	1500:1
Aktywny obszar wyświetlania (mm)	527.04(H) x 296.46(V)
ROZSTAW PIKSELI	0.2745(H) x 0.2745(V)
Powierzchnia matrycy	Anti-Glare with Circular Polarization
Wyświetlane kolory	16.7M
GŁĘBIA BITOWA	8 bits (6 bits + FRC)

FEATURES



IPS Panel with Wide Viewing Angle

Instantly optimize the screen colors and brightness to ensure that you enjoy every detail at its best.



EyesErgo

An eye care solution designed with ergonomics in mind. Includes Eye care & Ergonomic features.



Circular Polarization

Converts harsh digital rays into soft, naturally-polarized light to prevent eye strain and maximize visual comfort.



144Hz Game Ready

Thanks to the high refresh rate and adaptive-sync support, our gaming experience becomes completely smooth and free from interruptions.



Type C 65W Power Delivery

Built-in an USB Type-C connection with 65W power delivery allows you to effortlessly connect to and charge your devices




Delta-E (ΔE) ≤ 2

Factory pre-calibrated to guarantee a truly expressive hues and color accuracy.

Porty Wideo	1x HDMI™ 2.0b (FHD@144Hz) 1x DisplayPort 1.2a 1x Type-C (DP alt.) w/ 65W PD
KENSINGTON LOCK	Yes
Montaż VESA	75 x 75 mm
Typ zasilania	Internal Power Board
Regulacja (pochylenie)	-5° ~ 20°
WAGA (NETTO / BRUTTO)	5.35 kg (11.79 lbs) / 8 kg (17.64 lbs)
Uwagi	HDMI™ : 1920 x 1080 (Up to 144Hz) DisplayPort: 1920 x 1080 (Up to 144Hz) Type-C: 1920 x 1080 (Up to 144Hz) Delta-E (ΔE) ≤ 2 Support: HDMI™ CEC / MSI Power Link, KVM 1.0, FW Update; Non-Support: PIP/PBP

CONNECTIONS



1. 5-Way Navi-Key
2. 1x USB 5Gbps Type-B
3. 2x USB 5Gbps Type-A
4. 1x Type-C (DP alt.) w/ 65W PD
5. 1x DisplayPort 1.2a
6. 1x HDMI™ 2.0b (FHD@144Hz)
7. 1x Headphone-out
8. AC-in
9. Kensington-Lock