



SPECIFICATIONS

Panel Size	23.8"
Panel Resolution	1920 x 1080 (Full HD)
Refresh Rate	60Hz
Panel Type	IPS
Brightness (nits)	250 cd/m2
Aspect Ratio	16:9
Curvature	Flat
Active Display Area (mm)	527.04(H) x 296.46(V)
Pixel Pitch (H x V)	0.2745(H) x 0.2745(V)
Surface Treatment	Anti-glare
Display Colors	16.7M
Video ports	1x HDMI™ (1.4) 1x D-Sub (VGA)
Kensington Lock	Yes
VESA Mounting	100 x 100 mm
Power Type	Power Cable
Power Input	100~240V, 50~60Hz
Adjustment (Tilt)	-8° ~ 20°
Adjustment (Swivel)	-30° ~ 30°
Dimension (W x H x D)	539.5x385.7x228.9 mm (21.24 x 15.19 x 9.01 inch)
Carton Dimension (W X H X D)	606x409x196 mm (23.86x16.10x7.72 inch)
AUDIO PORTS	1x Headphone-out
SPEAKER	2x 1W
ADJUSTMENT (HEIGHT)	0 ~ 110mm
ADJUSTMENT (SWIVEL)	-30° ~ 30°
Compatibility	PC, Mac, PS5™, PS4™, Xbox, Mobile, Notebook * All trademarks and the registered trademarks are the property of their respective owners.
Note	HDMI™: 1920 x 1080 (Up to 75Hz) D-Sub: 1920 x 1080 (Up to 60Hz)
PANEL SIZE	27"
PANEL RESOLUTION	1920 x 1080 (FHD)
REFRESH RATE	75Hz
RESPONSE TIME	4ms (GTG Min.)
PANEL TYPE	VA
BRIGHTNESS (NITS)	250 cd/m2

FEATURES




Anti-Flicker technology

MSI Anti-Flicker technology provides a very comfortable viewing experience by reducing the amount of screen flicker.




Less Blue Light

Effectively reduce blue light which could cause serious long-term damage to your eyes.



Adjustable stand

Adjust the stand to the angle that is most suitable for you to keep yourself work comfortably



Display Kit Support

Providing the most convenient tool, the proper color & display mode to you while working with it everyday.



Type C Display

Allowing you to connect the latest devices more easily via USB Type C



Built-In Speaker

Built-in speakers allow you to listen clearly without connecting external speakers.



BUSINESSPRODUCTIVITYMONITOR

Modern MD271CP

BE YOUR WINDOW TO THE WORLD

VIEWING ANGLE	178°(H) / 178°(V)
CONTRAST RATIO	3000:1
sRGB	102% (CIE 1976)
ACTIVE DISPLAY AREA (MM)	597.888(H) X 336.312(V)
PIXEL PITCH (H X V)	0.3114(H) X 0.3114(V)
SURFACE TREATMENT	Anti-glare
DISPLAY COLORS	16.7M
COLOR BIT	8 bits
VIDEO PORTS	1x HDMI™ (1.4b) 1x Type C (DisplayPort Alternate)
KENSINGTON LOCK	Yes
POWER TYPE	External Adaptor (19V 3.42A)
VESA MOUNTING	75 x 75 mm
ADJUSTMENT (TILT)	-5° ~ 20°
DIMENSION (W X H X D)	611.5 x 250 x 533.7 mm (24.07 x 9.84 x 21.01 inch)
NOTE	HDMI™: 1920 x 1080 (Up to 75Hz) Type-C: 1920 x 1080 (Up to 75Hz)
CARTON DIMENSION (W X H X D)	720 x 212 x 466 mm (28.35 x 8.35 x 18.2735 inch)

CONNECTIONS



- 1. 1x Type C (DisplayPort Alternate)
- 2. 1x HDMI™ (1.4b)
- 3. 1x Headphone-out
- 4. 1x DC Jack