



## SPECIFICATIONS

Signal Frequency	72~216 KHz(H) / 48-144 Hz(V)
ADOBE RGB / DCI-P3 / SRGB	87% / 93% / 121% (CIE1976)
ASPECT RATIO	16:9
HDR SUPPORT	HDR Ready
USB Ports	2x USB 5Gbps Type-A 1x USB 5Gbps Type-B
AUDIO PORTS	1x Headphone-out
SPEAKER	3W x2
BRIGHTNESS (NITS)	300 cd/m2
POWER INPUT	100~240V, 50/60Hz
DYNAMIC REFRESH RATE TECHNOLOGY	Adaptive-Sync
Dimension with Stand (W x D x H)	613.49 x 200.81 x 401.72 mm (24.15 x 7.91 x 15.82 inch)
Dimension without Stand (W x D x H)	613.49 x 63.81 x 362.45 mm (24.15 x 2.51 x 14.27 inch)
CARTON DIMENSION (W X D X H)	613.49 x 63.81 x 362.45 mm (24.15 x 2.51 x 14.27 inch)
ADJUSTMENT (HEIGHT)	0 ~ 110 mm
WEIGHT (NW / GW)	6.4 kg (14.11 lbs) / 10.1 kg (22.27 lbs)
ADJUSTMENT (PIVOT)	-90° ~ 90°
ADJUSTMENT (SWIVEL)	-30° ~ 30°
ACCESSORIES	1x HDMI Cable (2.0b), 1x Type-C Cable (3.2 Gen 1), 1x USB Type-B to A Cable (3.2 Gen 1), 1x Power Cord, 1x Quick Guide, 4x VESA Wall Mount Screw, Color Report
PANEL SIZE	27"
PANEL RESOLUTION	2560 x 1440 (WQHD)
REFRESH RATE	144Hz
RESPONSE TIME	1ms (MPRT) / 4ms (GTG)
PANEL TYPE	IPS
VIEWING ANGLE	178°(H) / 178°(V)
CONTRAST RATIO	1500:1
ACTIVE DISPLAY AREA (MM)	597.736(H) x 335.664(V)
PIXEL PITCH (H X V)	0.2331(H) x 0.2331(V)
SURFACE TREATMENT	Anti-glare
DISPLAY COLORS	16.7M
COLOR BIT	8 bits (6 bits + FRC)

## FEATURES



### IPS Panel with Wide Viewing Angle

Instantly optimize the screen colors and brightness to ensure that you enjoy every detail at its best.



### EyesErgo

An eye care solution designed with ergonomics in mind. Includes Eye care & Ergonomic features.



### Circular Polarization

Converts harsh digital rays into soft, naturally-polarized light to prevent eye strain and maximize visual comfort.



### 144Hz Game Ready

Thanks to the high refresh rate and adaptive-sync support, our gaming experience becomes completely smooth and free from interruptions.



### Type C 65W Power Delivery

Built-in a USB Type-C connection with 65W power delivery allows you to effortlessly connect to and charge your devices




### Delta-E (ΔE) ≤ 2

Factory pre-calibrated to guarantee a truly expressive hues and color accuracy.

<b>VIDEO PORTS</b>	2x HDMI™ 2.0b (WQHD@144Hz) 1x DisplayPort 1.2a 1x Type-C (DP alt.) w/ 65W PD
<b>KENSINGTON LOCK</b>	Yes
<b>VESA MOUNTING</b>	75 x 75 mm
<b>POWER TYPE</b>	Internal Power Board
<b>ADJUSTMENT (TILT)</b>	-5° ~ 20°
<b>NOTE</b>	HDMI™: 2560 x 1440 (Up to 144Hz) DisplayPort: 2560 x 1440 (Up to 144Hz) Type-C: 2560 x 1440 (Up to 144Hz) Delta-E ( $\Delta E$ ) $\leq 2$ Support: HDMI CEC/ MSI Power Link, KVM 1.0, FW Update, PI App, M-Mate App; Non-Support: PIP/PBP

## CONNECTIONS



1. 5-Way Navi-Key
2. 1x Headphone-out
3. 2x HDMI™ 2.0b (FHD@144Hz)
4. 1x DisplayPort 1.2a
5. 1x Type-C (DP alt.) w/ 65W PD
6. 1x USB 5Gbps Type-B
7. 2x USB 5Gbps Type-A
8. AC-in
9. Kensington-Lock