

## SPECIFICATIONS

<b>Panel Size</b>	31.5"
<b>Panel Resolution</b>	3840 x 2160 (UHD)
<b>Refresh Rate</b>	240Hz
<b>Panel Type</b>	QD-OLED
<b>Brightness (nits)</b>	SDR: 300 cd/m2 HDR: 1000 (Peak.)
<b>Aspect Ratio</b>	16:9
<b>Curvature</b>	Flat
<b>Contrast Ratio</b>	1500000:1 (Typ.)
<b>Active Display Area (mm)</b>	699.48 (H) x 394.73 (V)
<b>Pixel Pitch (H x V)</b>	0.1814 (H) x 0.1814 (V)
<b>Surface Treatment</b>	Anti-Reflection
<b>Response time</b>	0.03ms (GtG)
<b>Display Colors</b>	1.07B, 10 bits
<b>Video ports</b>	2x HDMI™ 2.1 (UHD@240Hz) 1x DisplayPort 2.1a (UHBR20) 1x Type-C (DP alt.) w/ 98W PD
<b>DCR</b>	N/A
<b>Audio ports</b>	1x Headphone-out
<b>Viewing Angle</b>	178° (H) / 178° (V)
<b>Signal Frequency</b>	560.6~562.6KHz (H) / 48~240Hz (V)
<b>ACTIVATED RANGE</b>	48~240Hz
<b>Kensington Lock</b>	Yes
<b>VESA Mounting</b>	100 x 100 mm
<b>DYNAMIC REFRESH RATE TECHNOLOGY</b>	Adaptive-Sync
<b>Power Type</b>	Internal Power Board
<b>VESA ClearMR Certified</b>	VESA ClearMR 13000
<b>Power Input</b>	100~240V, 50/60Hz
<b>Signal Frequency</b>	30~270 KHz(H) / 40~120 Hz(V)
<b>USB ports</b>	2x USB 5Gbps Type-A 1x USB 5Gbps Type-B
<b>Adobe RGB / DCI-P3 / sRGB</b>	97% / 99% / 138% (CIE1976 Standard)
<b>ADOBE RGB / DCI-P3 / SRGB</b>	97.5% / 99% / 138.2% (CIE1976)
<b>HDR Support</b>	VESA DisplayHDR True Black 500
<b>ASPECT RATIO</b>	16:9
<b>Adjustment (Tilt)</b>	-5° ~ 15°
<b>Adjustment (Swivel)</b>	-30° ~ 30°
<b>HDR SUPPORT</b>	VESA DisplayHDR True Black 400

## FEATURES



### QD-OLED Display

MSI's renowned QD tech, combined with the latest OLED panel technology, these displays exhibit the best picture quality and incredible high contrast when gaming



### 4K 120Hz

4K clarity at 120Hz. Everything you see is sharper, and every movement is remarkably fluid.



### MSI M-Mate App

MSI M-Mate brings intuitive monitor control to your fingertips, bridging the gap between your monitor and Mac.



### Tandem OLED

The QD-OLED Penta Tandem™ panel integrates a 5-layer light-emitting structure to boost light efficiency by up to 30%.



### VisiClarity

VisiClarity masterfully integrates Anti-Glare Low Reflection technology to eliminate distracting light, providing a window of pure, undisturbed depth.



### DarkArmor Film

Delivers 40% deeper blacks and a 2.5x more scratch-resistant screen surface.



### AI Care Sensor

AI Care integrates AI sensors to dynamically optimize OLED protection based on real-time usage, making the system even smarter.



### USB Type-C Power Delivery 98W

Built-in an USB Type-C connection with 98W power delivery allows you to effortlessly connect to and charge your devices.


<b>USB Ports</b>	4x USB 5Gbps Type-A 1x USB 5Gbps Type-B
<b>Frameless Design</b>	Yes
<b>Audio Interface</b>	1x Headphone-out
<b>Adjustment (Height)</b>	0 ~ 110 mm
<b>SPEAKER</b>	2x 2.5W
<b>BRIGHTNESS (NITS)</b>	SDR: 250 HDR: 1000
<b>POWER INPUT</b>	100~240V, 50/60Hz
<b>Dimension with Stand (W x D x H)</b>	717.3 x 241.9 x 587.1 mm (28.24 x 9.52 x 23.11 inch)
<b>DYNAMIC REFRESH RATE TECHNOLOGY</b>	AMD FreeSync™ Premium Pro Technology
<b>Dimension without Stand (W x D x H)</b>	717.3 x 71.8 x 434.8 mm (28.24 x 2.83 x 17.12 inch)
<b>Dimension with Stand (W x D x H)</b>	611.1 x 200.6 x 560.3 mm (24.06 x 7.90 x 22.06 inch)
<b>Weight Without Stand</b>	6.6 kg (14.55 lbs)
<b>Dimension without Stand (W x D x H)</b>	611.1 x 73.0 x 367.9 mm (24.06 x 2.87 x 14.48 inch)
<b>CARTON DIMENSION (W X D X H)</b>	810 x 142 x 478 mm (31.89 x 5.59 x 18.82 inch)
<b>ADJUSTMENT (HEIGHT)</b>	0 ~ 150 mm
<b>Carton Dimension (W X D X H)</b>	985 x 169 x 513 mm (38.78 x 6.65 x 20.20 inch)
<b>WEIGHT (NW / GW)</b>	7 kg (15.43 lbs) / 10.5 kg (23.15 lbs)
<b>Accessories</b>	1x DisplayPort Cable (2.1a) 1x HDMI Cable (2.1) 1x Type-C Cable 1x USB Type-B to A Cable 1x Power Cord (C13) 1x Quick Guide, 4x VESA Wall Mount Screw 1x Fiber Cloth, 1x Color Report
<b>ADJUSTMENT (PIVOT)</b>	-90° ~ 90°
<b>ACCESSORIES</b>	1x HDMI™ Cable (2.1), 1x DisplayPort Cable (1.4a), 1x Type-C Cable (3.2 Gen 2), 1x USB Type-B to A Cable (3.2 Gen 1), 1x Power Cord (C13), 1x Quick Guide, 4x VESA Wall Mount Screw, 1x VESA Plate, 4x VESA Plate Screw, 1x VESA Adapter Kit, 1x Cable Clip, 1x Fiber Cloth, Color Report
<b>ADJUSTMENT (SWIVEL)</b>	-30° ~ 30°
<b>Note</b>	HDMI™: 3840 x 2160 (Up to 240Hz) DisplayPort: 3840 x 2160 (Up to 240Hz) Type-C: 3840 x 2160 (Up to 240Hz) Support: HDMI™ CEC, PIP/PBP, KVM
<b>Warranty</b>	3 years (including panel burn-in)
<b>PANEL SIZE</b>	26.5"
<b>PANEL RESOLUTION</b>	3840 x 2160 (UHD)
<b>REFRESH RATE</b>	120Hz
<b>RESPONSE TIME</b>	0.03ms (GtG)
<b>PANEL TYPE</b>	QD-OLED
<b>VIEWING ANGLE</b>	178°(H) / 178°(V)
<b>CURVATURE</b>	Flat
<b>CONTRAST RATIO</b>	1500000 : 1
<b>VIDEO PORTS</b>	2x HDMI™ 2.1 (UHD@120Hz) 1x DisplayPort 1.4a 1x Type-C (DP alt.) w/ 98W PD 1x Type-C (DP alt.) w/ 15W PD
<b>SURFACE TREATMENT</b>	Anti-Glare Low Reflection
<b>DISPLAY COLORS</b>	1.07B
<b>COLOR BIT</b>	10 bits

### NOTE

HDMI™: 3840 x 2160 (Up to 120Hz)  
DisplayPort: 3840 x 2160 (Up to 120Hz)  
Type-C: 3840 x 2160 (Up to 120Hz)  
Delta-E ( $\Delta E$ )  $\leq 2$   
Support: HDMI CEC/ MSI Power Link,  
OLED Care 3.0, KVM 1.0, FW Update,  
PIP/PBP

<b>ADJUSTMENT (TILT)</b>	-5° ~ 20°
<b>POWER TYPE</b>	Internal Power Board
<b>VESA MOUNTING</b>	100 x 100 mm
<b>KENSINGTON LOCK</b>	Yes
<b>ACTIVE DISPLAY AREA (MM)</b>	589.97(H) x 332.93(V)
<b>PIXEL PITCH (H X V)</b>	0.153(H) x 0.153(V)

## CONNECTIONS



1. Headphone-out
2. 2x HDMI™ 2.1 (UHD@120Hz)
3. DisplayPort 1.4a
4. Type-C (DP alt.) w/ 15W PD
5. Type-C (DP alt.) w/ 98W PD
6. USB 5Gbps Type-B
7. 2x USB 5Gbps Type-A
8. Kensington Lock
9. 2x USB 5Gbps Type-A
10. AC-in