



SPECIFICATIONS

DCR	100000000:1
Signal Frequency	54.2~121.5 KHz(H) / 48~120 Hz(V)
ADOBE RGB / DCI-P3 / SRGB	93% / 93% / 119% (CIE 1976)
ASPECT RATIO	16:9
HDR SUPPORT	N/A
USB Ports	N/A
Audio Interface	N/A
Webcam	N/A
SPEAKER	N/A
BRIGHTNESS (NITS)	300 cd/m²
POWER INPUT	100~240V, 50/60Hz
DYNAMIC REFRESH RATE TECHNOLOGY	Adaptive-Sync
Dimension with Stand (W x D x H)	489.4 x 182.36 x 384.77 mm (19.62 x 7.18 x 15.15 inch)
Dimension without Stand (W x D x H)	489.4 x 53.05 x 291.51 mm (19.62 x 2.09 x 11.48 inch)
CARTON DIMENSION (W X D X H)	567 x 120 x 365 mm (22.32 x 4.72 x 14.37 inch)
ADJUSTMENT (HEIGHT)	N/A
WEIGHT (NW / GW)	2.42 kg (5.34 lbs) / 3.96 kg (8.73 lbs)
ADJUSTMENT (PIVOT)	N/A
ADJUSTMENT (SWIVEL)	N/A
ACCESSORIES	1x HDMI Cable (1.4) , 1x Power Cord, 1x Quick Guide
PANEL SIZE	21.5"
PANEL RESOLUTION	1920 x 1080 (FHD)
REFRESH RATE	120Hz
RESPONSE TIME	1ms (MPRT) / 4ms (GtG)
PANEL TYPE	IPS
VIEWING ANGLE	178°(H) / 178°(V)
CONTRAST RATIO	1300:1
ACTIVE DISPLAY AREA (MM)	476.064(H) x 267.786(V)
PIXEL PITCH (H X V)	0.24795(H) x 0.24795(V)
SURFACE TREATMENT	Anti-glare
DISPLAY COLORS	16.7M, 8 bits (6 bits + FRC)
VIDEO PORTS	1x HDMI™ 1.4b (FHD@120Hz) 1x D-Sub (VGA)

FEATURES



IPS Panel with Wide Viewing Angle

Instantly optimize the screen colors and brightness to ensure that you enjoy every detail at its best.



EyeSergo

An eye care solution designed with ergonomics in mind. Includes Eye care & Ergonomic features.



Anti-Flicker Technology & Less Blue Light

With MSI Anti-Flicker technology & Less Blue Light, a stable output current for the monitor & effectively reduce blue light is provided to protect your eyes.



Less Blue Light

Effectively reduce blue light which could cause serious long-term damage to your eyes.



120Hz High Refresh Rate

Enjoy the high-quality entertainment with a smoother and flicker-free images.



VESA Mountable

To be mounted on the wall of your office & home with a VESA standard design which can make it completely invisible on a desk.

KENSINGTON LOCK	Yes
CURVATURE	Flat
VESA MOUNTING	100 x 100 mm
POWER TYPE	Internal Power Board
ADJUSTMENT (TILT)	-5° ~ 20°
NOTE	HDMI™: 1920 x 1080 (Up to 120Hz) D-Sub(VGA): 1920 x 1080 (Up to 60Hz) Support - ; Non Support: HDMI™ CEC/ MSI Power Link, PIP/PBP, KVM, FW Update

CONNECTIONS



- 1. 5-Way Navi Key
- 2. AC-in
- 3. 1x HDMI™ 1.4b (FHD@120Hz)
- 4. 1xD-Sub (VGA)
- 5. Kensington Lock